

SUSTAINABILITY METRICS PROGRAM

Guidebook

for development applications to the City of Richmond Hill

Revised May 22, 2024



Page intentionally left blank

Introduction

Over the last decades, cities and towns across the Greater Toronto and Hamilton Area (GTHA) have experienced significant and rapid growth. Municipalities play a pivotal role in responsibly managing growth and facilitating the development of communities that are environmentally, social, and economically sustainable.

To foster more sustainable new communities the Cities of Richmond Hill, Brampton, Vaughan, and Markham collaboratively offer a set of tools to evaluate and score the sustainability performance of development proposals, and encourage builders / developers to achieve a minimum level of performance. This included:

a) *Sustainability Metrics (Metrics):*

A set of performance metrics to encourage and evaluate the sustainability performance of new development, organized around the categories of Built Environment, Mobility, Natural Environment and Open Space, and Green Infrastructure and Building. Each of the over 120 Sustainability Metrics available to choose from are assigned a point value, and the combination of Metrics selected by the development proponent results in a Sustainability Score. Development proponents are able to select a combination of Metrics to achieve the minimum required Score. This enables the proponent to choose Metrics that best suit their individual property, project, and level of sustainability aspiration.

b) *Sustainability Assessment Tool (SAT):*

A digital tool that development proponents use to calculate their Sustainability Score by answering a series of questions regarding the Metrics achieved in their development proposal.

c) *Sustainability Score Thresholds (Thresholds):*

Performance levels achieved by the Sustainability Scores of a development proposal, and categorized as Bronze, Silver, or Gold.

The Sustainability Metrics Program is an important instrument to help implement both Provincial and Municipal land use planning, sustainability, and climate change goals and objectives. It facilitates creating healthy, complete, and sustainable communities that support quality of life for residents of all ages and abilities, energy efficiency and lower GHG emissions, more efficient use of land and infrastructure, local economic development, and cultural and natural heritage conservation. The Program also offers flexibility that enables development proponents to choose the sustainability approaches that best suits their project.

This Sustainability Metrics Program Guidebook is a living document that will be updated from time to time. Please refer to the Program webpage of the respective municipality for the latest version.

Note that Block Plans are not relevant to the City of Richmond Hill, in addition, there are some metrics not applicable to the City and those have been greyed out in the tables within the guidebook.



Oak Ridges Community Centre Silver LEED Certified



Elgin Mills Greenway Restoration

Page intentionally left blank

SUBMISSION REQUIREMENTS

As determined through a pre-submission meeting, development proposals may be required to include a copy of the Sustainability Metrics Summary Report as part of a complete planning application.

WHAT TYPE OF APPLICATIONS REQUIRE A SUSTAINABILITY SCORE?

- Draft Plans of Subdivision
- Site Plans (subject to site plan control by-law 137-093)

WHAT TYPE OF APPLICATIONS ARE EXEMPT?

- Site Plan applications that do not propose new construction
- Draft Plans of Subdivision for the purpose of subdividing large parcels of land for the sole purpose of creating lots for future employment, industrial, commercial, or institutional development, and which will require a subsequent Site Plan approval

DOES IT APPLY TO SITE-PLAN AMENDMENTS?

The Sustainability Metrics Program may apply to site-plan amendments on a case by case basis. Applicants will be advised of the requirements of the Sustainability Metrics as part of the City's standard Pre-Submission Meeting process.

IS THERE A MINIMUM REQUIRED SCORE?

Yes. Submissions must achieve a Score that falls at least within the Bronze Threshold. See below for the performance level thresholds for each submission type.

Performance Level	Sustainability Score Thresholds	
	Site Plan	Draft Plan
Bronze	41 - 61 points	27 - 40 points
Silver	62 - 75 points	41 - 49 points
Gold	76 or more points	50 or more points

PRE-SUBMISSION MEETING (Development Application Review Committee – DARC)

Applicants advised of Sustainability Metrics Program and associated minimum Sustainability Score requirements.

PLANNING APPLICATION SUBMISSION

Complete submission will include Sustainability Score & Summary. Submission to achieve at least a Bronze Score.

CIRCULATION / TECHNICAL REVIEW

Staff review plans/drawings and component studies to verify metrics achieved and Sustainability Score.

INFORMATION REPORT

Report on application's Preliminary Sustainability Score.

RE-SUBMISSIONS

Re-submission(s) will include an updated Sustainability Score & Summary.

RECOMMENDATION REPORT / SITE PLAN AGREEMENT

Report on applications Final Sustainability Score. Include Plan of Subdivisions or Site Plan condition(s).

DETAILED DESIGN

Demonstrate that Sustainability Score is being achieved.

Categories

The Sustainability Metrics are organized into four main categories: Built Environment, Mobility, Natural Environment and Open Space, Infrastructure and Buildings, in addition, a new category has been added, Innovation.

Built Environment (BE)

The indicators for Built Environment speak to how we inform places and connections within the development. The intensity and diversity of land uses influences decisions on where we live, work, and how we move around the community. A mix of housing types, amenities, and employment and live-work opportunities located within walking distance provides the opportunity for residents to meet their day-to-day needs without reliance on the private automobile. Further provision for life-cycle housing and accessible buildings allows residents to establish and remain in their communities throughout the various periods of their lives.

Mobility (MB)

The indicators of Mobility identify how a variety of transportation options must be available to residents to carry out their daily lives within and beyond the community. A sustainable community is one that encourages physical activity, facilitates active transportation, and supports public transit in place of automobile dependence. The most vulnerable population groups (children, elderly, disabled, and low-income individuals) are the most affected by choices available to them for mobility and access to services and amenities. Designing a safe, convenient, and accessible environment for walking and cycling encourages these alternative modes of transportation. Emphasis on mobility and active transportation not only reduces energy use and GHG emissions, but contributes directly to improving public health and the quality of life of residents.

Natural Environment and Parks (NE)

The natural environment, urban forest, and the open space system are essential components of a healthy, sustainable community. Firstly, the preservation and enhancement of the natural heritage system ensures the health of the environment and supports recreational and cultural opportunities in a community. Secondly, ensuring residents have convenient access to a connected and diverse range of open spaces, parks, and recreation facilities offers opportunities for improved public health and connections within the community.

Infrastructure and Buildings (IB)

The Infrastructure and Buildings indicators identify the means to maximize energy and water conservation and minimize the consumption of non-renewable resources. New buildings and communities should be designed with a focus on reducing water, waste, and energy use. Since human activity is the principal cause of elevated levels of greenhouse gases and demands on energy, water, and waste systems, the measures focus on reducing these impacts on both the built and natural environments.

Innovation (IN)

The innovation metric is intended to encourage true innovation resulting in real sustainability benefit. This new theme allows flexibility for users of the tool to propose innovative sustainability measures that are not specifically captured within the suite of metrics, but which provide a measurable sustainability benefit. This flexibility is intended to allow users to think progressively and outside of the box when proposing sustainability measures on their development site.

Indicators

The following are the performance indicators organized by category. Each performance indicator has associated metrics that are allocated a point score. The metrics reflect characteristics of a sustainable community and are designed to outline the required measures or standards for each category to ensure that the overall objectives of the Sustainability Metrics are achieved.

BUILT ENVIRONMENT	MOBILITY	NATURAL ENVIRONMENT AND PARKS
<ul style="list-style-type: none"> BE-1: Proximity to Amenities BE-2: Mixed-Use Development BE-3: Housing Diversity BE-4: Community and Neighbourhood Scale BE-5: Cultural Heritage Conservation BE-6: Urban Tree Canopy and Shaded Walkways/Sidewalks BE-7: Salt Management (<i>design and practices to reduce salt dependency</i>) BE-8: Carshare and Carpool Parking BE-9: Surface Parking Footprint BE-10: Electric Vehicle Charging Stations 	<ul style="list-style-type: none"> M-1: Block Length M-2: School Proximity to Transit and Cycling Network M-3: Intersection Density M-4: Walkable Streets M-5: Pedestrian Amenities M-6: Bicycle Parking M-7: Trails and Cycling Infrastructure M-8: Active Transportation Network M-9: Distance to Public Transit M-10: Traffic Calming 	<ul style="list-style-type: none"> NE-1: Tree Conservation NE-2: Soil Quantity and Quality for New Trees NE-3: Healthy Soils NE-4: Natural Heritage Connections NE-5: Natural Heritage System Enhancements NE-6: Supporting Pollinators NE-7: Dedicated Fruit/Vegetable Garden Space NE-8: Park Access NE-9: Stormwater Quantity NE-10: Stormwater Quality NE-11: Potable Water Use NE-12: Multi-purpose Stormwater Management
INFRASTRUCTURE AND BUILDINGS	INNOVATION	
<ul style="list-style-type: none"> IB-1: Buildings Designed/Certified Under Accredited “Green” Rating System IB-2: Accessibility for Multi-Unit Dwellings IB-3: Building Accessibility (Barrier Free Entry/Egress) IB-4: Embodied Carbon of Building Materials: Supplementary Cementitious Materials IB-5: Embodied Carbon of Building Materials: Life Cycle Assessment IB-6: Embodied Carbon of Building Materials: Material Efficient Framing IB-7: Heat Island Reduction: Non-Roof IB-8: Heat Island Reduction: Roof IB-9: Solar Gain Control IB-10: Solar Readiness IB-11: Energy Strategy IB-12: Building Energy Efficiency, GHG Reduction, and Resilience IB-13: Rainwater and Greywater Use IB-14: Back-Up Power IB-15: Extreme Wind Protection for Ground-Oriented Development IB-16: Sub-Metering of Thermal Energy and Water IB-17: Light Pollution Reduction IB-18: Bird-Friendly-Safe Design IB-19: Solid Waste 	<ul style="list-style-type: none"> I-1: Innovation 	

BUILT ENVIRONMENT

BE-1: PROXIMITY TO AMENITIES

Intent:	To encourage development within and near existing amenities, create more walkable communities, and reduce auto dependency.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	3 or more amenities are within 800 metres (equivalent to a 10 minute walk) of 75% of dwelling units (or the site for ICI applications only).	<p>In the Planning Justification Report (Draft Plan), Site Plan Drawing(s)/ Urban Design Brief (Site Plan), or other appropriate supporting documentation as requested by the City:</p> <p>Provide a map of the subject site with the proposed development overlaid and:</p> <ul style="list-style-type: none"> For residential and mix-use residential sites, highlight the area that accounts for 75% of the Dwelling Units (DU), and Identify the approximate geographic center. Identify the amenities within 800 metres and/or 400 metres radius from the geographic center.
Great:	+2 additional points (total 3 points)	3 or more amenities are within 400 metres (equivalent to a 5 minute walk) of 75% of dwelling units (or the site for ICI applications only).	<p>Note:</p> <ul style="list-style-type: none"> Amenities include: library, public parks and outdoor recreational facilities, public community/recreation centre, general retail, bank, place of worship, convenience store, restaurant, food retail (grocery store, supermarket), licensed adult/senior care, licensed child care, theatre, salon/barber shop, hardware store, laundry, medical office, dental office, post office, pharmacy, school, fitness center, and museum. Other amenities not specifically listed above may also be considered, where permitted by the City, provided that they meet the intent of the metric. One building can be considered to host multiple amenities (e.g. pharmacy included in a grocery store). If amenities are included in the proposed plan but have yet to be defined, use the zoning by-law coupled with best judgment (based on size, location and planning allocations) to assume the expected end-use of the planned amenity.
References:	<ul style="list-style-type: none"> Thinking Green (2018): 20, 21, 22 (Draft Plan of Subdivision) LEED ND (v4) SLL: Housing and Jobs Proximity LEED ND (v4) NPD: Mixed-Use Neighborhoods; NPD: Access to Civic and Public Space; NPD: Access to Recreation Facilities; NPD: Neighborhood Schools Community Wellbeing Framework (2018): Economic Domain, Complete Community 2A Whitby Green Standard v1 (2020): HH.V.3 (Site Plan) 		

BE-2: MIXED-USE DEVELOPMENT			
Intent:	To support locating housing, services, recreation, schools, shopping, jobs, work space, and other amenities on the same lot or block to facilitate wise use of land, make it easier for people to walk or cycle to these destinations, and reduce auto dependency.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	A mix of uses is provided on the same lot or block.	On the Draft Plan or Site Plan: <ul style="list-style-type: none"> Indicate the mix of uses (residential, institutional, commercial or industrial) within the proposed development.
References:	<ul style="list-style-type: none"> LEED ND (v4) NPD: Mixed-Use Neighborhoods; NPD: Compact Development Community Wellbeing Framework (2018): Economic Domain, Local Economy 4A 		

BE-3: HOUSING DIVERSITY			
Intent:	To encourage a range of housing options and facilitate aging in place.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	Ownership		<p>In the Planning Justification Report:</p> <ul style="list-style-type: none">Identify the percent (%) of the Ownership, Housing Type, and/or Accommodation Type included in the proposed development.Identify the total percent (%) by category should each add up to 100%. <p>On the Draft Plan or Site Plan, identify the following:</p> <ul style="list-style-type: none">Ownership Types,Housing Types, and/orAccommodation Types. <p>Note:</p> <ul style="list-style-type: none">For the definition of affordable housing, refer to the applicable Regional Official Plan, Richmond Hill Official Plan and Richmond Hill Affordable Housing Strategy, or Provincial Policy.Where there is a conflict between Provincial Policy and a municipal Official Plan, Provincial policy takes precedence.
	2 points	At least 10% of affordable/ low income or purpose-built rental housing is provided.	
Good:	Housing Type		
	1 point	Two of the housing typologies listed below are provided: <ul style="list-style-type: none">Single Detached,Semi Detached,Townhouse,Mid-rise,High-rise, and/orAdditional dwelling unit within a single detached, semi detached or townhouse dwelling (e.g. second unit, secondary suite).	
Great:	+1 additional point (total 2 points)	Three of the housing typologies listed below are provided: <ul style="list-style-type: none">Single Detached,Semi Detached,	

		<ul style="list-style-type: none"> • Townhouse, • Mid-rise, • High-rise, and/or • Additional dwelling unit within a single detached, semi detached or townhouse dwelling (e.g. second unit, secondary suite). 	
Excellent:	+ 1 additional point (total 3 points)	<p>Four or more of the housing typologies listed below are provided:</p> <ul style="list-style-type: none"> • Single Detached, • Semi Detached, • Townhouse, • Mid-rise, • High-rise, and/or • Additional dwelling unit within a single detached, semi detached or townhouse dwelling (e.g. second unit, secondary suite). 	
	Accommodation		
Good:	1 point	<p>Two accommodation types listed below are provided:</p> <ul style="list-style-type: none"> • Live-work, • Purpose-Built Rental, • Studio, • 1 bedroom, and/or • 2 or more bedrooms. 	
Great:	+1 additional point (total 2 points)	<p>More than two accommodation types below are provided:</p> <ul style="list-style-type: none"> • Live-work, • Purpose Built Rental, • Studio, • 1 bedroom, and/or • 2 or more bedrooms. 	
References:	<ul style="list-style-type: none"> • Thinking Green(2018): 29 (Draft Plan of Subdivision); 33 (Site Plan) • LEED ND (v4) NPD: Housing Types and Affordability • Community Wellbeing Framework (2018): Economic Domain, Affordability 1A • Whitby Green Standard v1 (2020): ELE1.1, ELE.V.1, ELE.V.2 (Draft Plan of Subdivision); ELE1.1, ELE 1.2, ELE.V.1, ELE.V.2 (Site Plan) 		

BE-4: COMMUNITY AND NEIGHBOURHOOD SCALE

Intent:	To focus on retail, personal, and community services within community core areas (neighbourhood centre and mixed-use node) so that people can meet their daily needs within their communities.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Excellent:	3 points	<p>Not applicable to Richmond Hill</p> <p>The proposed community form is based on the hierarchy below:</p> <ul style="list-style-type: none">Community: contains a mixed-use node central to the cluster of neighbourhoods that should include higher residential densities, retail, and employment opportunities, and served by public transit.	<p>In the Planning Justification Report include a figure of the proposed development and its surrounding area that highlights the:</p> <ul style="list-style-type: none">Community mixed use node and the cluster of surrounding neighbourhoods.Uses and densities within the mixed use node.Neighbourhood Centre and 400 metre radius.Uses and densities within the Neighbourhood Centre. <p>To be awarded a point for the 'Excellent' metric, both requirements must be met.</p>
	3 points	<p>Not applicable to Richmond Hill</p> <p>The proposed community form is structured to contain:</p> <ul style="list-style-type: none">Neighbourhood(s): defined by 400 metre radius (5 minute walk) from the neighbourhood centre to the neighbourhood perimeter with a distinct edge or boundary defined by other neighbourhoods or larger open spaces. ANDNeighbourhood Centre(s): a distinct centre with a compatible mix of uses that should include a neighbourhood park; high or medium residential densities; and retail or community facilities (e.g. school, library).	
References:	<ul style="list-style-type: none">Region of Peel, Health Background Study Development of a Health Background Study Framework, May 2011.Whitby Green Standard v1 (2020): TT.V.3 (Draft Plan of Subdivision).		

BE-5: CULTURAL HERITAGE CONSERVATION

Intent:	To conserve cultural heritage resources, including built heritage resources (listed or designated), cultural heritage landscapes (listed or designated), and archaeological resources.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Excellent:	3 points	The cultural heritage resource is conserved, and no elements that contribute to its cultural heritage value are altered, demolished, removed, or relocated (excluding temporary removal for restoration purposes).	<p>In the Cultural Heritage Impact Assessment and/or Heritage Conservation Plan and/or other documents acceptable by the City:</p> <ul style="list-style-type: none"> Provide an outline of the cultural heritage attributes that contribute to the cultural heritage value and confirm that no portions of the resource that contribute to its cultural heritage value are to be altered, demolished, removed, or relocated. <p>Note: For the purposes of this metric, “conserved” means:</p> <ul style="list-style-type: none"> The identification, protection, management and use of cultural heritage resources in a manner that ensures their cultural heritage value or interest is retained under the <i>Ontario Heritage Act</i>. This may be achieved by the implementation of recommendations set out in a Cultural Heritage Impact Assessment, Conservation Plan, Archaeological Assessment, and/or other documentation accepted by the City. Mitigated measures and/or alternative development approaches can be included in these plans and assessments. Conservation and conserve have corresponding meanings. The Standards and Guidelines for the Conservation of Historic Places in Canada is the guiding document for the conservation of cultural heritage resources in Canada.
Great:	2 points	A portion of the cultural heritage resource is retained, and the integrity of the cultural heritage resource is conserved.	<p>In the Cultural Heritage Impact Assessment and Heritage Conservation Plan, or other document accepted by the City:</p> <ul style="list-style-type: none"> Provide an outline of the attributes that contribute to the cultural heritage value, identification of the portion(s) of the cultural heritage resource to be conserved, and rationale demonstrating that the integrity of the cultural heritage resource is being conserved. <p>For the purposes of this metric, “integrity” means:</p> <ul style="list-style-type: none"> A measure of its wholeness and intactness of the cultural heritage values and attributes. Examining the conditions of integrity requires assessing the extent to which the property/cultural heritage resource includes all elements necessary to express its cultural heritage value; is of adequate size to ensure the complete representation of the features and processes that convey the cultural heritage resource’s significance; and the extent to which it suffers from adverse effects of development and/or neglect.

			<ul style="list-style-type: none"> Integrity should be assessed within the Cultural Heritage Impact Assessment, or other documentation accepted by the City.
Good:	1 point	Where a cultural heritage resource will be relocated, it will be moved to a visually prominent location within the proposed development.	In the Cultural Heritage Impact Assessment and/or Heritage Conservation Plan and/or other documents acceptable to the City: <ul style="list-style-type: none"> Identify the proposed location of the cultural heritage resource that ensures its visual prominence.
Good:	1 point	Where reusable materials from a cultural heritage resource are being removed, a portion will be salvaged and reused within the proposed development.	In the Cultural Heritage Impact Assessment and/or Heritage Conservation Plan and/or other documents acceptable to the City: <ul style="list-style-type: none"> Identify the materials that will be salvaged and how they will be reused on site. Note: <ul style="list-style-type: none"> The reuse of the salvaged materials should also be demonstrated in appropriate supporting documents (e.g. site plan drawings, landscape plan).
References:	<ul style="list-style-type: none"> CommunityWellbeing Framework (2018): Cultural Domain, Cultural Vitality 1B, Sense of Belonging 2B Whitby Green Standard v1 (2020): CC1.2 (Draft Plan of Subdivision), CC1.3 (Site Plan) LEED ND v4 GIB: Historic Resource Preservation and Adaptive Reuse Thinking Green (2018): 31 (Draft Plan of Subdivision); 36 (Site Plan) 		

BE-6: URBAN TREE CANOPY AND SHADED WALKWAYS/SIDEWALKS

Intent:	To provide street trees that create a more pleasant pedestrian environment and mitigate the urban heat island effect. Street trees provide ecosystem services and health benefits.		
Applicable to:	<input type="checkbox"/> Block Plan	<input type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	Trees will shade at least 50% of the walkway/sidewalk lengths within 10 years.	On a Landscape Plan: <ul style="list-style-type: none"> Identify the total length of existing and or planned sidewalks in the proposed development, and the total length of existing and or planned sidewalks with trees abutting the sidewalk, measured as a percentage of sidewalk length.
Great:	+1 additional point (total 2 points)	Trees will shade at least 75% of the walkway/sidewalk lengths within 10 years.	Note: <ul style="list-style-type: none"> New trees will be selected in accordance with the Richmond Hill Standards and Specifications Manual.
Great:	2 points	Trees will shade at least 50% of parking areas within 10 years.	On a Landscape Plan: <ul style="list-style-type: none"> Identify the total parking area and the total parking area that will be shaded by the tree canopy and quantify as a percentage.

Good:	1 point	Street trees are provided on both sides of street at intervals averaging no more than 9 metres, where supported by the City.	<p>On a Landscape Plan:</p> <ul style="list-style-type: none">Identify the distance intervals of street trees. <p>For further guidance, see Richmond Hill Standards and Specifications Manual.</p>
Excellent:	+ 2 additional points (total 3 points)	Street trees are provided on both side of streets within the project at distance intervals averaging 8 metres or less, where supported by the City.	
References:	<ul style="list-style-type: none">LEED ND (v4) NPD: Tree-Lined and Shaded StreetscapesToronto Green Standard v3 Tier I: Ecology (EC1.3) (CF, LR, MHR); Tier II: Ecology (EC1.5)(LR, MHR)		

BE-7: SALT MANAGEMENT *(design and practices to reduce salt dependency)*

Intent:	To reduce the use of salt and its negative impacts on water bodies, soil, vegetation, wildlife, buildings, and vehicles. Reducing salt use also helps protect the natural environment from salt exposure.		
Applicable to:	<input type="checkbox"/> Block Plan	<input type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	2 points	<p>At least two of the following measures are provided:</p> <ul style="list-style-type: none"> 2 to 4% grade throughout all outdoor parking lots to ensure proper drainage and limit refreezing. Use of salt-tolerant species of vegetation in areas that will receive meltwater. Use of trees as windbreaks around the site perimeter. Heated or covered walkways near building entrances. <p>AND</p> <ul style="list-style-type: none"> A well-planned, designated snow storage area(s) is provided to ensure meltwater drains as intended in the site design. 	<p>On a Landscape Plan:</p> <ul style="list-style-type: none"> Document the two or more measures being used to promote salt reduction, and identify the designated snow storage area. <p>Note: Landscape Ontario Horticultural Trades Association lists the following as salt tolerant plants:</p> <ul style="list-style-type: none"> Sea Thrift - <i>Armeria maritima</i>, Karl Foerster Reed Grass – <i>Calamagrostis acutifolia</i> 'Karl Foerster', Helen Allwood Pinks – <i>Dianthus pulminarius</i> x <i>allwoodii</i>, Blue Lyme Grass – <i>Elymus arenarius</i>, Fountain Grass – <i>Pennisetum alopecuroides</i>. <p>Additional suitable plants can be found using the Network of Nature CanPlant database, a resource to help identify ecologically-appropriate native plant species suitable for landscape design.</p> <p>To be awarded a point for the 'Good' metric, both requirements must be met.</p>
References:	<ul style="list-style-type: none"> Parking Lot Design Guidelines to Promote Salt Reduction. Lake Simcoe Region Conservation Authority, 2017. 		

BE-8: CARSHARE AND CARPOOL PARKING

Intent:	To encourage carpooling and reduce dependence on single-occupant vehicle trips. Carpooling contributes to GHG emission reduction, less air pollution, less congestion, and improved social connections.		
Applicable to:	<input type="checkbox"/> Block Plan	<input type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	Dedicate 3% of parking spaces on-site to carpooling and/or carshare/zip car (does not apply to compact cars). Provide preferred parking for these vehicles by incorporating signage and/or pavement markings.	On the Site Plan: <ul style="list-style-type: none">Quantify the total parking spaces included per building on the site.Quantify the total parking spaces that are dedicated to carshare/zip car or carpooling.Identify the dedicated parking spaces and highlight proximity/preferred location relative to building entry. Note: <ul style="list-style-type: none">Documentation of an agreement with the carshare provider may be requested by the City
Great:	+1 additional point (total 2 points)	Dedicate 5% of parking spaces on-site to carpooling and/or carshare/zip car (does not apply to compact cars). Provide preferred parking for these vehicles by incorporating signage and/or pavement markings.	
References:	<ul style="list-style-type: none">Toronto Green Standard v3 Tier I: Air Quality (AQ1.2) (CF, MHR)LEED ND (v4) LT: Reduced Parking FootprintLEED BD+C (v4) LT: Reduced Parking FootprintWhitby Green Standard v1 (2020): TT1.8 (Site Plan)Thinking Green (2018): 29 (Site Plan)		

BE-9: SURFACE PARKING FOOTPRINT

Intent:	To promote efficient use of land and to support on-street retail and pedestrian-oriented built environments. Surface parking can block access and visibility to homes and businesses. Minimizing or carefully locating surface parking can result in more pedestrian-friendly and valuable streetscapes.		
Applicable to:	<input type="checkbox"/> Block Plan	<input type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	All surface parking on site is located at the side or rear of buildings.	On the Site Plan: <ul style="list-style-type: none"> Identify the building frontage and the surface parking location(s). Note: <ul style="list-style-type: none"> Should aim for no more than 20% of the total development area dedicated to off-street surface parking facilities, and surface parking lot should not be larger than 2 acres.

Great:	2 points	Less than 15% of the total developable area is provided to parking at grade and is located at the rear or side of buildings.	<p>On the Site Plan:</p> <ul style="list-style-type: none"> Identify the building frontage and the surface parking location(s). Calculate the total area dedicated to surface parking/parking facilities and the total area of the proposed development. Identify the percent (%) of site area allocated to surface/facility parking.
Excellent:	3 points	All new on-site parking is provided below grade or in structured parking, and no surface parking is provided.	<p>Note:</p> <ul style="list-style-type: none"> For this metric, surface parking facilities include ground-level garages unless they are under habitable building space. Underground or multi-story parking facilities within the habitable building space and on-street parking spaces are exempt from this limitation. Spaces dedicated to short-term parking and pickup/drop-off are exempt from the requirements of the excellent metric.
References:	<ul style="list-style-type: none"> LEED ND (v4) LT: Reduced Parking Footprint LEED BD+C (v4) LT: Reduced Parking Footprint Whitby Green Standard v1 (2020): TT1.9 (Site Plan) Thinking Green (2018): 31 (Site Plan) 		

BE-10: ELECTRIC VEHICLE CHARGING STATIONS			
Intent:	To facilitate the use of electric vehicles.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	3 points	Electric vehicle supply equipment (EVSE) is provided to serve 10% of parking spaces.	<p>On the Site Plan and Landscape Plan:</p> <ul style="list-style-type: none"> Provide the number of total parking spaces included per building on the site. Provide the number of total parking spaces that will be provided with EVSE. Provide the percentage of parking spaces that will be provided with EVSE. <p>For Site Plans and Draft Plan Applications, provide:</p> <ul style="list-style-type: none"> A Letter of Commitment from a qualified professional (e.g. electrical engineer, landscape architect, architect) and the owner/developer/builder confirming the number of EV charging stations and the percent of parking spaces with EVSE.
Great:	+2 additional points (total 5 points)	Electric vehicle supply equipment (EVSE) is provided to serve 20% of parking spaces.	<p>Note:</p> <ul style="list-style-type: none"> <i>Electric vehicle supply equipment (EVSE)</i> is defined by the Ontario Electrical Safety Code as the complete assembly consisting of cables, connectors, devices, apparatus, and fittings, installed for power transfer and information

Excellent:	2 points	At least 50% of the parking spaces are designed and constructed to permit future EVSE installation (e.g. rough-in).	<p>exchange between the branch circuit and the electric vehicle. For the requirements of this metric, applicants are encouraged to consult with the City to determine the appropriate level or equivalent for EVSE.</p> <ul style="list-style-type: none"> • <i>Rough-in provisions</i> are defined as empty raceways starting in a junction box in the electrical room and terminating in a junction box central to each parking floor. Raceways will be empty to accommodate future wiring. • Establishing electric vehicle charging stations are achieved by agreement at the development stage and implementation at the building stage. It is important for developers and builders to agree to install electrical vehicle charging stations prior to commitment.
References:	<ul style="list-style-type: none"> • Toronto Green Standard v3 Tier I: Air Quality (AQ1.3) (CF, MHR) • Whitby Green Standard v1 (2020): TT1.10 (Draft Plan of Subdivision); TT1.15 (Site Plan) • LEED BD+C v4 LT: Electric Vehicles • Thinking Green (2018): 27 (Draft Plan of Subdivision); 30 (Site Plan) 		

MOBILITY

M-1: BLOCK LENGTH

Intent:	To develop shorter blocks that increase permeability offering pedestrians and cyclists multiple routes to reach their destination(s) and to allow blocks with the flexibility to accommodate both residential and commercial lot sizes. Walkable blocks improve connectivity and reduce dependence on vehicles.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	75% of block lengths do not exceed 250 metres.	<p>On the Draft Plan:</p> <ul style="list-style-type: none"> Provide the measurement of the block lengths for all blocks included in the proposed development. Identify and confirm the percentage (%) of block lengths that are less than 250 metres. <p>Note:</p> <ul style="list-style-type: none"> Blocks are determined by roads/streets, and not pathways or trails.
Great:	+1 additional point (total 2 points)	All block lengths do not exceed 250 metres.	<p>On the Draft Plan:</p> <ul style="list-style-type: none"> Provide the measurement of the block lengths and the block perimeter lengths for all blocks included in the plan. Provide confirmation that all block lengths are less than 250 metres. <p>Note:</p> <ul style="list-style-type: none"> Blocks are determined by roads/streets, and not pathways or trails.
Excellent:	+1 additional point (total 3 points)	All blocks do not exceed 80 metres x 150 metres in size.	<p>On the Draft Plan:</p> <ul style="list-style-type: none"> Provide the measurement of the block sizes and confirm there are no blocks greater than 80 metres x 150 metres. <p>Note:</p> <ul style="list-style-type: none"> Blocks are determined by roads/streets, and not pathways or trails.
References:	<ul style="list-style-type: none"> Thinking Green (2018): 19 (Draft Plan of Subdivision) Region of Peel, Health Background Study (2011), Core Element 4: Street Connectivity Whitby Green Standard v1 (2020): TT1.7 (Draft Plan of Subdivision) 		

M-2: SCHOOL PROXIMITY TO TRANSIT AND CYCLING NETWORK

Intent:	To encourage students to walk and/or cycle to school to reduce vehicle use, traffic congestion at school sites, and promote active transportation. Walking, cycling, and transit use reduce result in GHG emissions and air pollution and provide health benefits.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	All public schools are located within a 400 metre walking distance to transit routes and/or dedicated cycle networks.	On the Draft Plan, within the Planning Justification Report and/or other appropriate supporting documentation as requested by the City, provide a map that illustrates: <ul style="list-style-type: none">• Radial circles to illustrate 400 m and 200 m from each school,• Location of the proposed development,• Existing or planned public school(s),• Existing or planned transit stops, and• Existing or planned dedicated cycle network(s).
Great:	+1 additional point (total 2 points)	All public schools are located within a 200 metre walking distance to transit routes and/or dedicated cycle networks.	
References:	<ul style="list-style-type: none">• Region of Peel, Healthy Background Study Framework (2011)• Whitby Green Standard v1 (2020): TT.V.3 (Draft Plan of Subdivision)		

M-3: INTERSECTION DENSITY

Intent:	To encourage shorter blocks and increase permeability and connectivity offering pedestrians and cyclists multiple routes to reach their destination(s). Greater intersection density results in more walkable blocks, improves connectivity and reduces dependence on vehicles.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	Not applicable to Richmond Hill Provide for 40-50 multi-use trail, path, and/or street intersections per square kilometre (km ²).	In the Urban Design Brief or Planning Justification provide a map that: <ul style="list-style-type: none"> • Highlights the eligible intersections. • Delineates each square kilometre (km²). • Identifies the number of eligible intersections within the proposed development per sq.km. Note: <ul style="list-style-type: none"> • Eligible intersections include: Multi-use trails/paths, cycling paths, walking paths, publicly accessible streets, laneways, and transit right-of-ways
Great:	+1 additional point (total 2 points)	Not applicable to Richmond Hill Provide for 51-60 multi-use trial, path, and/or street intersections per square kilometre (km ²).	

Excellent:	+2 additional points (total 4 points)	<p>Not applicable to Richmond Hill</p> <p>Provide for 61 or more multi-use trail, path, and/or street intersections per square kilometre (km²).</p>	<ul style="list-style-type: none"> Non-Eligible intersections generally include intersections where you must enter and leave an area through the same intersection, for example, cul-de-sacs and gated street entrances A square kilometre (km²) is defined as the total area of land available for development, similar to the net developable area, and its calculation excludes water bodies, parks larger than 0.2 hectares, natural heritage system lands, public facility campuses, airports, existing and proposed 400-series highways, and rail yards.
References:	<ul style="list-style-type: none"> LEED ND (v4) NPD: Connected and Open Community Whitby Green Standard v1 (2020): TT.V.1 (Draft Plan of Subdivision) 		

M-4: WALKABLE STREETS

Intent:	To encourage walking through the provision of safe and comfortable street environments. Walkable streets reduce dependence on vehicles, improve safety, enhance connectivity, and are an important component for healthy and complete communities.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	2 points	Where not a mandatory requirement, and where supported by the City, provide/ extend continuous sidewalks or multi-use trails on both sides of public and private roads/streets.	<p>On the Draft Plan or Site Plan:</p> <ul style="list-style-type: none"> Provide continuous sidewalk or multi-use trails on both sides of public and private roads/streets. Verify and document that the sidewalks comply with Richmond Hill Standards and Specifications Manual.
References:	<ul style="list-style-type: none"> LEED (v4) ND NPD: Walkable Streets Whitby Green Standard v1 (2020): TT1.5 (Draft Plan of Subdivision); TT1.6 (Site Plan) Thinking Green (2018): 23 (Draft Plan of Subdivision, Site Plan) 		

M-5: PEDESTRIAN AMENITIES

Intent:	To promote the installation of amenities that contribute to a positive pedestrian experience and ensure destinations in communities are connected through convenient, safe, and accessible pedestrian connections. Walkable connections improve the physical and mental wellbeing of residents of all ages and abilities, help to reduce dependence on motor vehicle use, and limit air pollution and GHG emissions.		
Applicable to:	<input type="checkbox"/> Block Plan	<input type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	<p>Pedestrian connections are provided between the building entry and other destinations on the site and to destinations on adjacent properties.</p> <p>AND</p> <p>1 type of pedestrian amenity is consistently included along on-site connections.</p>	<p>On the Landscape Plan:</p> <ul style="list-style-type: none"> Identify the pedestrian connections that link a building entry to destinations on site and to destinations on adjacent properties. Highlight the pedestrian amenities provided along the pedestrian connections. <p>Note:</p> <ul style="list-style-type: none"> Amenities include: benches, pedestrian oriented lighting, waste receptacles, public art, map stands, interpretive/commemorative signage, and weather shelters. Destinations include: walkways, transit stops, parking areas (vehicle and bicycle), existing trails or pathways, schools, community centres, or commercial areas. Pedestrian connections are only required to be built to the site boundary and not beyond (to establish future connection possibilities). Privately owned public spaces (POPs) would incorporate multiple pedestrian amenities and can be a proposal considered under the Innovation metric. To be awarded a point for the 'Good' metric, both requirements must be met.
Great:	+1 additional point (total 2 points)	More than 1 type of pedestrian amenity is consistently included along on-site connections and between the site and adjacent destinations.	
References:	<ul style="list-style-type: none"> Toronto Green Standard v3 Tier I: Air Quality (AQ3.1) (CF, MHR) 		

M-6: BICYCLE PARKING

Intent:	To facilitate cycling and reduce dependence on motor vehicle use.		
Applicable to:	<input type="checkbox"/> Block Plan	<input type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	Bicycle parking spaces are provided at a rate of 20% higher than the City's Parking and Transportation Demand Management Strategy.	On the Site Plan drawing identify the:

Great:	+1 additional point (total 2 points)	Bicycle parking spaces are provided at a rate 50% higher than the City's Parking and Transportation Demand Management Strategy.	<ul style="list-style-type: none">• Building types included in the proposed development (e.g. mixed-use, residential, commercial, retail, and institutional).• Location of bicycle parking provided.• Total number of bicycle parking spaces required by the City's Parking and Transportation Demand Management Strategy.• Total number of bicycle parking spaces provided per building.• Percent of total bicycle parking provided relative to the City's Parking and Transportation Demand Management Strategy.• Distance to entrances or access from bicycle parking.• Location of the showers and change rooms within the building <p>Note:</p> <ul style="list-style-type: none">• To be awarded a point for the 'Excellent' metric, both requirements must be met.• For additional information, see the City's Parking and Transportation Demand Management Strategy and Standards and Specifications Manual
Excellent:	2 points	Bicycle parking is located in close proximity to building entrances. Short-term bicycle parking is located within 25 metres of building entrances if outdoors. Long-term bicycle parking is within 50 metres of an exit or entrance area. AND All bicycle parking is weather protected.	
Excellent	1 point	1 shower and change room are provided (for men and women) per 30 bicycle parking spaces associated with non-residential development.	
References:	<ul style="list-style-type: none">• Community Wellbeing Framework (2018): Environment Domain, Mobility 3B• Whitby Green Standard v1 (2020): TT1.2, TT1.12, TT1.13 (Site Plan)• Thinking Green Item (2018): 25 (Site Plan)• Toronto Green Standard v3 Tier I: Air Quality (AQ2.2, AQ2.3, AQ2.4) (CF, MHR); Tier II: Air Quality (AQ2.5) (MHR)		

M-7: TRAILS AND CYCLING INFRASTRUCTURE

Intent:	To implement pedestrian and cycling infrastructure to further promote active forms of transportation. Walking and cycling reduces GHG emissions and air pollution, and provides health benefits.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	Advance the objectives of Richmond Hill's Transportation Master Plan by implementing the active transportation/trails-related objectives of the Plan.	<p>In the Transportation Study, and/or other appropriate supporting documentation as requested by the City:</p> <ul style="list-style-type: none"> • Identify any existing or planned multi-use trails and/or bicycle lanes located in the proposed development. • If applicable, highlight the multi-use trails and/or bicycle lanes that comply with the City's Transportation Master Plan. • If applicable, highlight the additional features that advance the objectives of the active transportation/trails-related objectives of the Transportation Master Plan (e.g. trailheads, trail signs, information signage, and/or seating areas).
References:	<ul style="list-style-type: none"> • Community Wellbeing Framework (2018): Environment Domain, Mobility 3B • Whitby Green Standard v1 (2020): TT1.2 (Draft Plan of Subdivision, Site Plan) • Thinking Green (2018): 25 (Draft Plan of Subdivision); 26 (Site Plan) 		

M-8: ACTIVE TRANSPORTATION NETWORK

Intent:	To promote active transportation through the provision of public multi-purpose trails/paths and cycling infrastructure. Cycling results in carbon savings and less air pollution. It also provides health benefits.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	2 points	<p>100% of residents/jobs are within 400 metres of:</p> <ul style="list-style-type: none"> An existing public multi-use trail/path or cycling infrastructure; or A municipally approved public multi-use trail/path or cycling infrastructure (identified in a Council approved trail/cycling master plan, but not yet constructed); or A proposed public multi-use trail/path or cycling infrastructure that is proposed within the development. 	<p>In the Traffic Impact Study, Transportation Demand Management Plan, or Transportation Study:</p> <ul style="list-style-type: none"> Provide a map showing the subject lands, a 400 metre buffer from the boundaries of the subject lands (the project boundary), as well as any existing or planned multi-use trail/path or cycling networks. <p>Note:</p> <ul style="list-style-type: none"> These points are only awarded if a multi-use trail/path or cycling network is included in the project boundary.
References:	<ul style="list-style-type: none"> Community Wellbeing Framework (2018): Environment Domain, Mobility 3B Richmond Hill Transportation Master Plan 		

M-9: DISTANCE TO PUBLIC TRANSIT

Intent:	To promote and support alternative transportation modes to personal automotive vehicle use. Transit-oriented communities reduce vehicle-kilometres traveled and associated emissions, have reduced traffic casualty rates and support walking and cycling which improves community health.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	<p>The site is within 800 metres walking distance to an existing or planned commuter rail, light rail, bus rapid transit or subway with frequent stops.</p> <p style="text-align: center;">OR</p> <p>The site is within 400 metres walking distance to 1 or more existing or planned bus stops with frequent service.</p>	<p>In the Urban Design Brief and/or Transportation Study (Draft Plans) and Traffic Impact Study and/or Transportation Demand Management Plan (Site Plan), include:</p> <ul style="list-style-type: none"> Include a map that shows the 200 meter, 400 meter, and/or 800 meter radii and the existing or planned commuter rail, subway, light rail, and bus stops with frequent service. <p>Note:</p>

Great:	+1 additional point (total 2 points)	<p>The site is within 400 metres walking distance to an existing or planned commuter rail, light rail, bus rapid transit, or subway with frequent stops.</p> <p style="text-align: center;">OR</p> <p>The site is within 200 metres walking distance to 1 or more bus stops with frequent service.</p>	<ul style="list-style-type: none"> <i>Frequent Service</i> is defined as transit with trips in intervals no greater than 30 minutes during peak times per line per direction and available during hours of typical building operation.
References:	<ul style="list-style-type: none"> LEED ND (v4) LT: Access to Quality Transit Community Wellbeing Framework (2018): Environment Domain, Mobility 3B Whitby Green Standard v1 (2020): TT.V.3, TT1.6 (Draft Plan of Subdivision); TT.V.3, TT1.7 (Site Plan) Thinking Green (2018): 26 (Draft Plan of Subdivision); 27 (Site Plan) 		

M-10: TRAFFIC CALMING

Intent:	To encourage active transportation through the provision of safe, walkable streets by reducing car speeds. Walkable streets and traffic calming measures can provide a safer and more comfortable streetscape to cyclists and pedestrians, and help to reduce traffic speeds, volumes, and related emissions.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	75% of new local streets/roads are designed with traffic calming strategies. <i>(Applicable to Residential and Mixed-Use only)</i>	In a Transportation Study or Traffic Calming Report: <ul style="list-style-type: none">Highlight the new residential-only streets and new non-residential/mixed-use streets in the proposed development, as applicable.Identify the percentage (%) of street length (broken out by residential only and non-residential/mixed use) that includes street calming strategies developed in consultation with municipal transportation planning staff.Provide a drawing identifying the traffic calming strategies that are included in the project. Note: Traffic calming strategies include but are not limited to: <ul style="list-style-type: none">Neckdowns,Centre island narrowing,Raised crosswalks,Traffic circles and roundabouts, and/orSpeed display boards/vehicle activated traffic calming signs (VATCS).
Great:	+2 additional points (total 3 points)	100% of new local streets/roads are designed with traffic calming strategies. <i>(Applicable to Residential and Mixed-Use only)</i>	
Good:	1 point	50% of new non-residential and/or mixed-use streets are designed with traffic calming strategies. <i>(Applicable to Residential, Mixed-Use, and ICI)</i>	
Great:	+2 additional points (total 3 points)	75% of new non-residential and/or mixed-use streets are designed with traffic calming strategies. <i>(Applicable to Residential, Mixed-Use, and ICI)</i>	
References:	<ul style="list-style-type: none">Whitby Green Standard v1 (2020): TT1.4 (Draft Plan of Subdivision, Site Plan)		

NATURAL ENVIRONMENT & PARKS

NE-1: TREE CONSERVATION

Intent:	To support the conservation of healthy mature trees and the associated ecological, economic, and health benefits. Preserving trees can be a cost-effective method to improve the overall appearance of a community while providing ecological and climate change benefits.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	3 points	Preserve 25% of healthy mature trees in situ on site.	<p>On an Arborist Report:</p> <ul style="list-style-type: none"> Identify all trees as per the City's requirements. Label all the healthy mature trees, including hedgerows, on the subject site, the trees that will be protected, moved or, removed as the City's requirements. Provide the percent (%) of healthy tableland trees that will be protected in-situ.
Great:	+2 additional points (total 5 points)	Preserve 50% of healthy, mature trees in situ on site or preserve 100% of healthy hedgerows in situ on site.	<p>Note:</p> <p>This metric applies for healthy, mature trees on the developable portion of the site (e.g. not in the protected natural heritage system).</p> <ul style="list-style-type: none"> Healthy mature trees include those evaluated as being fair or above by a certified Arborist and at least 20 cm DBH (diameter at breast height), or in accordance with the most current City by-law. <p>For additional information see by-law 41-07; a by-law to prohibit or regulate the injuring or destruction of trees on private property and Richmond Hill Standards and Specifications Manual.</p>
References:	<ul style="list-style-type: none"> Town of Whitby Green Standard v1 (2020): LUN1.4 (Draft Plan of Subdivision, Site Plan) 		

NE-2: SOIL QUANTITY AND QUALITY FOR NEW TREES

Intent:	To provide soil quantity and quality that enables new trees to thrive. Higher amounts of good quality soil help ensure the success of vegetation.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	2 points	<p>Provide a minimum of 30 cubic metres (m³) of soil for each new tree and a minimum of 1 metre uncompact soil depth.</p> <p>Where there is a grouping of trees, provide a minimum of 20 cubic metres (m³) of soil for each new tree, and a minimum of 1 metre of uncompact soil depth, or equivalent municipal standard.</p>	<p>On the Landscape Plan:</p> <ul style="list-style-type: none"> Identify the tree planting locations, soil volume, soil depth, and soil quality that will be provided for each tree. <p>Note:</p>

Great:	+ 2 additional points (total 4 points)	Provide 25% more than the total soil volume required by the City's Standards and Specifications Manual.	<ul style="list-style-type: none">If the initial submission of the Draft Plan of Subdivision is too early in the development review process to provide the aforementioned details, provide a Letter of Commitment from a landscape architect and the owner/ developer/ builder confirming that the metric requirement will be achieved and that details will be provided in the Landscape Plan during subsequent submissions. For further guidance, see the Richmond Hill Standards and Specifications Manual.
Excellent	2 points	Provide uncompact topsoil layer of tree pits, trenches, or planting beds with the following properties: <ul style="list-style-type: none">Organic matter content of 10 to 15% by dry weight and a pH of 6.0 to 8.0.A minimum depth of 1 metre, or in accordance with municipal standards, whichever is higher.Provide adequate drainage.	
References:	<ul style="list-style-type: none">TRCA (2012) Preserving and Restoring Healthy Soils Best Practice Guide for Urban ConstructionCredit Valley Conservation (2017) Healthy Soils Guideline for the Natural Heritage SystemVineland Research (2019) Ontario Landscape Tree Planting GuideSustainable Technologies Evaluation Program (STEP) (2017) Compost Amended Planting Soil SpecificationsCommunity Wellbeing Framework (2018): Environment Domain, Natural Systems 2AToronto Green Standard v3 Tier I: Ecology (EC1.1, EC1.2) (CF, LR, MHR); Tier II: Ecology (EC1.6) (LR, MHR)		

NE-3: HEALTHY SOILS

Intent:	To ensure that new development contains healthy soil quality and quantity to help restore the natural functions of soils and vegetation and to help ensure the soil is appropriate for the proposed plantings. Limiting disturbance of healthy soils protects soil horizons and maintains soil structure, as well as supports biological communities (above-ground and below-ground).		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	A minimum topsoil depth of 200 millimetres is provided across the entire site (excluding paved surfaces).	On a Landscape Plan: <ul style="list-style-type: none">Identify the minimum topsoil depth that is provided across the entire site.
Great:	+1 additional point (total 2 points)	A minimum topsoil depth of 300 millimetres is provided across the entire site (excluding paved surfaces).	
References:	<ul style="list-style-type: none">TRCA Preserving and Restoring Healthy Soils Best Practice Guide for Urban ConstructionCVC’s Healthy Soil Guidelines for Natural Heritage SystemSustainable Technologies Evaluation Program (STEP) (2017) Compost Amended Planting Soil SpecificationsThinking Green (2018): 5 (Draft Plan of Subdivision, Site Plan)		

NE-4: NATURAL HERITAGE CONNECTIONS

Intent:	To provide connections to nature and green spaces to benefit human health through proximity or access, and to minimize the amount of the natural heritage that is backlotted by residential development.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	2 points	Provide physical public connections (such as public access blocks, single loaded roads, parks, sidewalks, etc.) to 25% of the length of the natural heritage system that abuts the proposed development (interface between development and natural heritage systems).	On a Landscape Plan or Site Plan: <ul style="list-style-type: none">Identify the natural heritage features within the proposed development.Identify all roads, sidewalks, pathways, and parks adjacent to any natural heritage features, and include the length of each that directly abuts the natural heritage feature.Determine the length of natural heritage system (all natural heritage features) within the site.Determine what percentage (%) of the natural heritage system with potential access to the site has been provided with physical public connections. Note: <ul style="list-style-type: none">Percentage (%) of the natural heritage system is determined by the length of the natural heritage system perimeter.Private yards (e.g. backlotting) and parking lots will not be counted as part of the physical public connection border.
Great:	+2 additional point (total 4 points)	Provide physical public connections (such as public access blocks, single loaded roads, parks, sidewalks, etc.) to 50% or more of the length of the natural heritage system that abuts the proposed development (interface between development and natural heritage systems).	
References:	<ul style="list-style-type: none">Thinking Green Item (2018): 2 (Draft Plan of Subdivision, Site Plan)		

NE-5: NATURAL HERITAGE SYSTEM ENHANCEMENTS

Intent:	To improve natural heritage system, particularly with respect to wildlife habitat and/or ecological functions.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	Provide and implement a Woodland Management Plan within and/or abutting the subject lands, where not already required by the City.	Provide a Woodland Management Plan in accordance with a Terms of Reference that has been agreed upon by the City.

Good:	1 point	Provide and implement an Invasive Species Management Plan for a natural heritage feature, where not already required by the City.	Provide an Invasive Species Management Plan in accordance with a Terms of Reference that has been agreed upon by the City.
Good:	1 point	Provide habitat structure(s) for species at risk, such as bird structures, butterfly boxes, and hibernaculum.	<p>In the Natural Heritage Evaluation:</p> <ul style="list-style-type: none"> • Outline the design and ecological function of the habitat structure(s). • Provide a figure illustrating the proposed locations of the habitat structure(s). • Provide a design specification of the habitat structure(s).
Great	2 points	Provide a form of natural heritage restoration/enhancement that provides a net ecological gain, above City requirements.	<p>In the Natural Heritage Evaluation:</p> <ul style="list-style-type: none"> • Outline the natural heritage restoration/enhancement, its ecological function, and how it achieves a net ecological gain above Richmond Hill's requirements. • Provide a figure illustrating the proposed location(s) of the natural heritage restoration/enhancement. • Provide a design specification for the natural heritage restoration/enhancement.
Excellent	5 points	Design and deliver a linear continuous/uninterrupted naturalized corridor, not already identified as a natural heritage feature in the Official Plan or through technical studies, which creates a functional linkage between at least two natural heritage features.	<p>In the Natural Heritage Evaluation:</p> <ul style="list-style-type: none"> • Outline the design and ecological function (e.g. wildlife corridor, amphibian passage, and meadow-way/grassland) of the linkage. • Provide a plan/figure illustrating the proposed linkage including dimensions, landscape treatment, and the natural heritage features it will be connecting, which will be used to inform detailed design.
References:	<ul style="list-style-type: none"> • TRCA, Invasive Plant List • Credit Valley Conservation, Native Plants for Pollinators • Toronto Pollinator Protection Strategy, City of Toronto • Community Wellbeing Framework (2018): Environment Domain, Natural Systems 2A • Whitby Green Standard v1 (2020): LUN1.8, LUN1.9, LUN.V.1, LUN.V.2 (Draft Plan of Subdivision); LUN1.10, LUN1.11, LUN.V.2, LUN.V.3, LUN.V.4 (Site Plan) • Thinking Green Item (2018): 1 (Draft Plan of Subdivision, Site Plan) 		

NE-6: SUPPORTING POLLINATORS

Intent:	To provide landscape materials that support and provide habitat for pollinators (e.g. birds, bees, butterflies). Without pollinators, much of the food we eat and the natural habitats we enjoy would not exist. Pollinators are under increasing stress due to habitat loss, invasive species, diseases, pesticides, and climate change.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	Native plants that support pollinators make up 25% or more of total quantity of plants proposed on the landscape plan.	For Draft Plans, provide a Letter of Commitment from a landscape architect and the owner/developer/builder confirming that the metric requirement will be achieved and that details will be provided in the Landscape Plan during subsequent submissions.
Great:	+1 additional point (total 2 points)	Native plants that support pollinators make up 50% or more of the total quantity of plants proposed on the landscape plan.	<p>On the Landscape Plan:</p> <ul style="list-style-type: none"> Identify the species and proposed quantities of native plants (trees, shrubs, perennials, etc.) that support pollinators on the plant list. Provide a calculation that illustrates the total percentage of native pollinator plants by dividing the number of native pollinator plants by the total quantity of all plants. <p>Note:</p> <ul style="list-style-type: none"> Pollinator plant species must be selected from the Credit Valley Conservation “Native Plants for Pollinators”, Toronto and Region Conservation Authority “Maintaining Your Pollinator Habitat” or alternative list approved by the City. Consider native plants that support all stages of a pollinators lifecycle
References:	<ul style="list-style-type: none"> Credit Valley Conservation, Native Plants for Pollinators, https://cvc.ca/wp-content/uploads/2017/04/17-uo-nativeplantsforpollinators-booklet-v8-web.pdf Toronto Pollinator Protection Strategy, City of Toronto, https://www.toronto.ca/wp-content/uploads/2018/05/9676-A1802734_pollinator-protection-strategy-booklet.pdf TRCA, Maintaining Your Pollinator Habitat, https://trca.ca/app/uploads/2016/04/PollinatorMaintenanceGuide_WEB.pdf TRCA, Creating Habitat, https://trca.ca/app/uploads/2016/04/2602-Stewardship_Habitat-SinglePg_PRESS.pdf Community Wellbeing Framework (2018): Environment Domain, Natural Systems 2A Whitby Green Standard v1 (2020): LUN1.7 (Draft Plan of Subdivision); LUN1.8, LUN1.9 (Site Plan) Toronto Green Standard v3 Tier I: Ecology (EC3.1) (CF, LR, MHR) 		

NE-7: DEDICATED FRUIT/VEGETABLE GARDEN SPACE

Intent:	To promote locally grown food, improve physical and mental wellbeing, and to encourage social interaction.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	2 points	<p>For multi-unit residential developments:</p> <ul style="list-style-type: none"> Provide garden space that is equal to 25 square metres (m²) (or 269 square feet (ft²)) of the rooftop or total landscaped site area. Provide a shed for gardening equipment storage. Provide a water source for the garden space. <p>For ground-oriented residential developments:</p> <p><i>With yards:</i></p> <ul style="list-style-type: none"> For each residential lot, provide a raised garden bed that is at least 12 inches (30cm) tall, 4 feet (1.2 m) wide, and 6 feet (1.8 m) long. <p><i>Without yards:</i></p> <ul style="list-style-type: none"> For each unit, provide container gardens that can accommodate 15 gallons (57L) of soil and are at least 12 inches (30cm) deep. 	<p>On the Landscape Plan:</p> <ul style="list-style-type: none"> Determine the total landscaped area of the project. Specify total area of garden space provided. Identify supportive garden infrastructure (e.g. shed and water source). <p>Note:</p> <ul style="list-style-type: none"> Garden space is defined as land and/or an alternative mechanism with a growing medium that will be used to cultivate plants for food. Garden beds must provide at least 12 inches of garden soil depth (this garden soil will be provided above the standard topsoil). Achieving this metric for ICI applications can be considered for meeting the Innovation metric requirements.
References:	<ul style="list-style-type: none"> Living Community Challenge 1.2, Place: Urban Agriculture LEED ND (v4) NPD: Local Food Production Town of Whitby Green Standard v1 (2020): LSF1.1 (Draft Plan of Subdivision); LSF1.1, LSF.V.1 (Site Plan) 		

NE-8: PARK ACCESS

Intent:	To promote visual and physical access to public parks and to make it easier for people of all ages and abilities to integrate physical activity and social interaction as part of their daily activity.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	3 points	<p><i>For Brampton, Richmond Hill, and Markham:</i> Provide 2 road frontages for each park (e.g. urban square, parkette, and neighborhood park) and,</p> <p><i>For City of Vaughan only:</i> A minimum of 50% of a park has a public street frontage.</p>	<p>On the Site Plan, Urban Design Brief, or Landscape Plan (Draft Plans):</p> <ul style="list-style-type: none"> Highlight the urban squares, parkettes, neighborhood parks, linear parks, and community parks included within the application. <p><i>For Vaughan only:</i></p>

Great:	+3 additional points (total 6 points)	<p><i>For Brampton, Richmond Hill, and Markham:</i> Provide 3 or more road frontages for all parks.</p> <p><i>For City of Vaughan only:</i> Approximately 50-70% of a park has a public street frontage.</p>	<ul style="list-style-type: none"> Identify the linear metres of public road frontages for each park type, and percentage of park that has public road frontage.
References:	<ul style="list-style-type: none"> Whitby Green Standard v1 (2020): HH1.2 (Draft Plan of Subdivision, Site Plan) 		

NE-9: STORMWATER QUANTITY

Intent:	To support a treatment-train approach to stormwater management, emphasizing source and conveyance controls to promote infiltration, evaporation, and/or re-use of runoff and/or rainwater. Managing stormwater at the early stages of the treatment-train can provide more resilient communities and reduce risks of downstream flooding and erosion.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
	Note: requirements below are applicable to Richmond Hill only.		
Good:	2 points	Retain runoff volume from the 40 27 millimetre rainfall event on public and private sites.	In the Functional Servicing Report, Stormwater Management Plan, Master Environmental Servicing Plan, and/or other appropriate supporting documentation as requested by the City: <ul style="list-style-type: none">List and describe the design measures used to retain stormwater runoff on-site. Measures could include (but are not limited to) Low Impact Development (LID) measures, stormwater management ponds, etc.Highlight the location of design measures (if any) on the applicable plan.Confirm that the quantity and flood controls are in accordance with applicable City and conservation authority requirements.Provide calculations and signoff by a qualified professional (e.g. professional engineer) quantifying the amount of runoff that will be retained on site. Note: <ul style="list-style-type: none">For infrastructure-related design measures such as LIDs and stormwater management ponds, the City may request or require additional documentation and/or agreements regarding maintenance of this infrastructure.
Great:	+2 additional points (total 4 points)	Retain runoff volume from the 45 32 millimetre rainfall event on public and private sites.	
Excellent:	+3 additional points (total 7 points)	Retain runoff volume from the 25 40 millimetre rainfall event on public and private sites.	
References:	<ul style="list-style-type: none">City of Richmond Hill Standards and Specifications Manual (Division H)Toronto Green Standard v3 Tier II: Water Balance, Quality, and Efficiency (WQ 2.2) (LR, MHR); Tier III: Water Balance, Quality, and Efficiency (WQ 2.3) (LR, MHR), (WQ 2.1) (CF)TRCA's Stormwater Management CriteriaTRCA and CVC (2012) Low Impact Development Stormwater Management Planning and Design GuideVaughan's Urban Design GuidelinesWhitby Green Standard v1 (2020): SW1.1, SW1.5 (Draft Plan of Subdivision); SW1.1, SW1.6 (Site Plan)Thinking Green (2018): 8 (Draft Plan of Subdivision); 12 (Site Plan)LEED ND v4 GIB: Rainwater Management		

NE-10: STORMWATER QUALITY

Intent:	To protect receiving water bodies from water quality degradation that may result from development and urbanization. Controlling the quality of stormwater can provide for improved quality of receiving water bodies, resulting in fewer algae blooms, longer swimming seasons, and a variety of other ecological benefits.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	Remove 81% or more of Total Suspended Solids (TSS) from all runoff leaving the site during a 25 millimetre rainfall event (based on the post-development level of imperviousness).	In the Functional Servicing Report, Stormwater Management Plan, Master Environmental Servicing Plan, and/or other appropriate supporting documentation as requested by the City: <ul style="list-style-type: none">Provide a list and description of the filtration measures used to treat the stormwater runoff on-site. Strategies could include (but are not limited to): stormwater management ponds, oil-grit separators (ETV certified), bioswales, or filters (to be used only in exceptional circumstances if other measures are unsuitable). <ul style="list-style-type: none">Highlight the design measures (if any) on a plan.Quantify the percent (%) of TSS removed from a 25 mm rainfall event.
Great:	+4 additional points (total 5 points)	Remove 90% or more of Total Suspended Solids (TSS) from all runoff leaving the site during a 25 millimetre rainfall event (based on the post-development level of imperviousness).	
References:	<ul style="list-style-type: none">Toronto Green Standard Tier I: Water Balance, Quality & Efficiency (WQ 3.1) (CF, LR)TRCA Stormwater Management CriteriaTRCA and CVC Low Impact Development Stormwater Management Planning Design (2012)Whitby Green Standard v1 (2020): SW1.1, SW1.3 (Draft Plan of Subdivision); SW1.1, SW1.4 (Site Plan)LEED ND v4 GIB: Rainwater ManagementLEED BD+C v4 SS: Rainwater ManagementThinking Green (2018): 9 (Draft Plan of Subdivision); 11 (Site Plan)		

NE-11: POTABLE WATER USE

Intent:	To facilitate the conservation and efficient use of potable water.		
Applicable to:	<input type="checkbox"/> Block Plan	<input type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	2 points	Reduce potable water used for irrigation by 50%, compared to a mid-summer baseline case.	<p>Provide a Letter of Commitment from a qualified professional (e.g. architect, mechanical engineer, landscape architect) and the owner/developer/builder to:</p> <ul style="list-style-type: none"> Confirm the project will be designed to reduce potable water requirements for irrigation. Confirm the percent (%) reduction in potable water used to irrigate, relative to a mid-summer baseline case. For information on how to achieve this credit refer to LEED v4 BD+C WE Credit: Outdoor Water Use Reduction Option 2 and use the calculation tool to demonstrate. Confirm the strategies used to reduce potable water demands. Strategies include: <ul style="list-style-type: none"> Drought tolerant, native/ or adaptive vegetation that requires little to no water in the local climate. Use of high-efficiency irrigation, such as drip irrigation. Use of captured rainwater for irrigation. <p>If captured rainwater is used, provide a Letter from a Qualified professional (mechanical engineer) confirming the proposed cistern size and the calculations to demonstrate the volume of captured water expected.</p>
Great:	+4 additional points (total 6 points)	No potable water is used for irrigation.	<ul style="list-style-type: none"> Provide the documentation as requested for "Good", unless no irrigation is being installed. In the case where no irrigation is installed, provide a Letter of Commitment from qualified professionals (property managers, building owners, site owners) confirming that no irrigation will be installed past the establishment period and that sod will be allowed to go dormant and brown in off-season months.
References:	<ul style="list-style-type: none"> LEED ND (v4) WE: Indoor Water Use Reduction; WE: Outdoor Water Use Reduction LEED BD+C (v4.1) WE : Outdoor water use reduction Toronto Green Standard v3 Tier II: Water Balance, Quality & Efficiency (WQ 4.3) (CF, LR, MHR) Community Wellbeing Framework (2018): Environment Domain, Natural Systems 2C Whitby Green Standard v1 (2020): SW1.7 (Site Plan) 		

NE-12: MULTI-PURPOSE STORMWATER MANAGEMENT

Intent:	To enhance the public use value of stormwater management facilities.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	Introduce beautification measures/amenities that beautify stormwater management ponds (e.g. public art, interpretive signage).	<p>In the Functional Servicing Report or Stormwater Management Plan:</p> <ul style="list-style-type: none"> Identify beautification measures (public art, interpretative signage, visually pleasing infrastructure, etc.) included within the proposed development that are above and beyond City's landscape specifications as found in the Richmond Hill Standards and Specifications Manual. <p>Note:</p> <ul style="list-style-type: none"> Any proposed measure must not reduce the performance function of the stormwater management pond. Fountains are not acceptable beautification measures.
References:	<ul style="list-style-type: none"> Appendix E - Stormwater Management Pond Design Guidance of TRCA SWM Criteria document (2012) 		

INFRASTRUCTURE & BUILDINGS

IB-1: BUILDINGS DESIGNED/CERTIFIED UNDER ACCREDITED “GREEN” RATING SYSTEM

Intent:	To recognize leadership and efforts to achieve independent third-party green certification systems that demonstrate high sustainability performance. Sustainability certification systems provide recognizable and verified certifications demonstrating to the public a high degree of sustainability performance is being achieved.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 to 7 points (1 point per building, total 7 points available)	One or more buildings on site will be enrolled in a third-party green certification system.	<ul style="list-style-type: none">Provide a Letter of Commitment signed by a qualified professional (e.g. architect, professional engineer, LEED professional) and the owner/developer/builder that:<ul style="list-style-type: none">Identifies the green rating system that will be achieved and certified for the building(s).Confirms registration for the third-party green rating system (e.g. receipt of the registration fees).For Energy Star: A signed Partnership Agreement with EnerQuality acknowledging their roles and responsibilities as a partner and documenting their commitment to meet program requirements. <p>Note:</p> <ul style="list-style-type: none">Acceptable third-party accredited green rating systems include:LEEDv4 or LEEDv4.1 (not including LEED for Commercial Interiors)Certified Passive House BuildingLiving Building Challenge 4.0CaGBC Zero Carbon Building Design Standard Version 3 (June 2022)Energy Star CanadaOne Planet LivingLEED ND v4
Excellent:	1 additional point per building (to a maximum of 7 buildings)	One or more buildings on site will be enrolled in multiple third-party green certification systems.	
Good:	2 points	The development will achieve LEED ND v4 (or equivalent).	
Excellent:	4 points	The development will achieve One Planet Living rating (or equivalent).	
References:	<ul style="list-style-type: none">Sustainable Design and Construction Policy for Municipal BuildingsCanada Green Building Council Zero Carbon Building Design Standard Version 2, March 2020York Region Sustainable Development through LEED Incentive ProgramThinking Green (2018): 12 (Draft Plan of Subdivision); 15 (Site Plan)		

IB-2: ACCESSIBILITY FOR MULTI-UNIT DWELLINGS

Intent:	To enable a wide spectrum of people to live within and access new buildings, regardless of ability. To provide accessibility to occupants beyond the Ontario Building Code, which mandates that a barrier-free path of travel is included in 15% of Multi-Residential Units.		
Applicable to:	<input type="checkbox"/> Block Plan	<input type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	2 points	For multi unit-residential buildings, design a minimum of 25% of the Dwelling Units (DU) to achieve accessibility features required in the Ontario Building Code.	Provide a Letter of Commitment signed by a qualified professional (e.g. architect, engineer, accessibility consultant) that identifies how the metric has been achieved.
Great:	+1 additional points (total 3 points)	For multi unit-residential buildings, design a minimum of 35% of the Dwelling Units (DU) to achieve basic accessibility features required in the Ontario Building Code.	On the Site Plan: <ul style="list-style-type: none"> Identify the total number of units, the number of units that achieve the accessibility features required in the Ontario Building Code, and the total percentage of units that achieve the accessibility features required in the Ontario Building Code.
References:	<ul style="list-style-type: none"> LEED ND (v4) NPD: Visitability and Universal Design Whitby Green Standard v1 (2020): ELE.V.3 (Site Plan) Thinking Green (2018): 32 (Site Plan) 		

IB-3: BUILDING ACCESSIBILITY (BARRIER FREE ENTRY/EGRESS)

Intent:	To enable a wide spectrum of people and access to new buildings, regardless of age or ability. Inclusive buildings and neighborhoods expand the number of potential users, thereby increasing value. They also enable more diversity in age of occupants and visitors.		
Applicable to:	<input type="checkbox"/> Block Plan	<input type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	50% of emergency exits above the Ontario Building Code requirements are designed to be barrier free.	On a Site Plan drawing: <ul style="list-style-type: none">Identify all building entrances and exits.Quantify as a percentage (%) all building entrances and exits that will be barrier free as per the Ontario Building Code.
Great:	+1 additional points (total 2 points)	100% of all entries and exits above the Ontario Building Code requirements are designed to be barrier free.	
References:	Not applicable		

IB-4: EMBODIED CARBON OF BUILDING MATERIALS: SUPPLEMENTARY CEMENTITIOUS MATERIALS

Intent:	To increase the growing awareness of the importance of addressing the embodied carbon and other GHG emissions associated with building materials. The GHG emissions generated from the production of building materials can be significant, but GHG reductions are possible through material selection and design. Often, lower impact materials are also more cost-effective.		
Applicable to:	<input type="checkbox"/> Block Plan	<input type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	All concrete on site must have a minimum of 20% Supplementary Cementitious Materials (SCMs).	A Letter of Commitment from a qualified professional (e.g. professional engineer or architect) confirming that concrete will have a SCM content of 20% or more (Good)/ 40% or more (Great). Note: <ul style="list-style-type: none">Supplementary cementitious materials (SCMs) contribute to the properties of hardened concrete through hydraulic or pozzolanic activity. Examples include fly ashes, slag cement (ground, granulated blast-furnace slag) and silica fume. They can be used individually with Portland or blended cement or in different combinations. SCMs are often added to concrete to make concrete mixtures more economical, reduce permeability, increase strength, or influence other concrete properties.Embodied carbon can be defined as the lifetime greenhouse gas (GHG) emissions associated with material. It is life cycle thinking applied to a product, and includes GHG's associated with the manufacture, transportation and installation of a product, any GHG's related to product maintenance and renewal, and GHG's associated with the end of life of the product.
Great:	+1 additional point (total 2 points)	All concrete on site must have a minimum of 40% Supplementary Cementitious Materials (SCMs).	
References:			

IB-5: EMBODIED CARBON OF BUILDING MATERIALS: LIFE CYCLE ASSESSMENT

Intent:	To increase the growing awareness of the importance of addressing the embodied carbon and other GHG emissions associated with building materials. The GHG emissions generated from the production of building materials can be significant, but GHG reductions are possible through material selection and design. Often, lower impact materials are also more cost-effective.		
Applicable to:	<input type="checkbox"/> Block Plan	<input type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Great:	1 point	Report embodied carbon emissions for the structural and envelope materials for every Part 3 building on site. To develop the report, use lifecycle assessment software such as Athena Impact Estimator for Buildings Life Cycle	<p>On a Site Plan Drawing:</p> <ul style="list-style-type: none"> Identify the building(s) that is being assessed, its use (residential, commercial, institutional), the estimated gross floor area, the number of storeys, and the number of dwelling units (If residential).

		<p>Assessment (LCA) software (or equivalent). Consider three methods to reduce the embodied carbon content of each building reviewed.</p> <p>Note: Part 3 residential buildings are large and complex buildings, four storeys and taller, and greater than 600 square metres in building area.</p>	<ul style="list-style-type: none"> Confirm the number of Part 3 buildings on site that are being assessed (whichever is greater). Provide a LCA report declaring the materials that are anticipated to be used and the estimated total embodied carbon emissions of these materials used for the structure and envelope. <p>Note:</p> <ul style="list-style-type: none"> Embodied carbon can be defined as the lifetime greenhouse gas (GHG) emissions associated with material. It is life cycle thinking applied to a product, and includes GHG's associated with the manufacture, transportation and installation of a product, any GHG's related to product maintenance and renewal, and GHG's associated with the end of life of the product. <p>Athena Impact Estimator for Buildings: https://calculatelca.com/software/impact-estimator/</p> <p>Refer to the Zero Carbon Building Standard for further guidelines on LCA assessments: https://www.cagbc.org/cagbcdocs/zerocarbon/CaGBC_Zero_Carbon_Building_Standard_EN.pdf</p>
Excellent:	+4 additional points (total 5 points)	Commit to employing one or more carbon reduction strategies that would result in a 10% reduction in embodied carbon of the design.	In addition to the documentation requirements above, provide a Letter of Commitment from a qualified professional (e.g. professional engineer or architect) stating the intent to use one or more low carbon design strategies to reduce embodied carbon.
References:	<ul style="list-style-type: none"> Canada Green Building Council, Net Zero Carbon Building Standard Version 2. March, 2020 Athena Sustainable Materials Institute (September 2019) http://www.athenasmi.org/wp-content/uploads/2019/09/About_WBLCA.pdf 		

IB-6: EMBODIED CARBON OF BUILDING MATERIALS: MATERIAL EFFICIENT FRAMING

Intent:	To increase the growing awareness of the importance of addressing the embodied carbon and other GHG emissions associated with building materials.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Great:	3 points	<p>For all low-rise wood-framed construction, utilize at least 3 of the following advanced framing measures:</p> <ul style="list-style-type: none"> Pre-cut framing packages Engineered Floor Joist Single Top-Plates Two Stud Corners Stud spacing greater than 406 mm (16") on any storey Ceiling joist spacing greater than 406 mm (16") on any storey 	<p>Provide a Letter of Commitment from the owner/developer/builder committing to practice material efficient framing and listing the measures that will be employed from the eligible measures provided.</p> <p>Note:</p> <ul style="list-style-type: none"> Embodied carbon can be defined as the lifetime greenhouse gas (GHG) emissions associated with material. It is life cycle thinking applied to a product, and includes GHG's associated with the manufacture, transportation and installation of a product, any GHG's related to product maintenance and renewal, and GHG's associated with the end of life of the product.

		<ul style="list-style-type: none"> Floor joist spacing greater than 406 mm (16") on any storey. All corners have no more than 2 studs. 	<ul style="list-style-type: none"> Modular construction approach can assist in confirming these requirements.
References:	<ul style="list-style-type: none"> Athena Sustainable Materials Institute (September 2019) http://www.athenasmi.org/wp-content/uploads/2019/09/About_WBLCA.pdf 		

IB-7: HEAT ISLAND REDUCTION: NON-ROOF			
Intent:	To reduce ambient surface temperatures and reduce the urban heat island effect, which contributes to climate adaptation and more comfortable, livable communities.		
Applicable to:	<input type="checkbox"/> Block Plan	<input type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	2 points	<p>For both Residential and Non-Residential Development:</p> <p>Use one or more of the following strategies to treat 50% of the site's non-roof hardscaping:</p> <ul style="list-style-type: none"> High albedo paving materials with an initial solar reflectance of at least 0.33 or SRI of 29. Open grid paving with at least 50% perviousness. Shade from existing or new tree canopy within 10 years of landscape installation. Shade from architectural structures that are vegetated or have an initial solar reflectance of at least 0.33 at installation or an SRI of 29. Shade from structures with energy generation. <p style="text-align: center;">OR</p> <p><i>For non-residential development only:</i></p> <ul style="list-style-type: none"> Have a minimum of 75% of at-grade parking spaces under a cover. 	<p>On the Landscape Plan:</p> <ul style="list-style-type: none"> Identify the area of the total hardscape on the site (excluding building footprint) Identify the strategies, locations, and size used to reduce heat island from the hardscape area (e.g. underground/covered parking, hardscape shading, hardscape materials with an SRI greater than 29, and open grid pavers with perviousness greater than 50%). The following products have an SRI greater than 29: <ul style="list-style-type: none"> White-coated gravel on the built-up roof (SRI 79), White coating on a metal roof (SRI 82), White cement tile (SRI 90), New gray concrete (SRI 35). For unit pavers and open grid/ pervious paving, provide examples of the products that are intended for the design and provide manufacturer's documentation with the SRI or solar reflectance value to confirm. <p>Determine the percent (%) of the hardscape area that has employed heat island reduction strategies, relative to the total hardscape area.</p> <p>Note:</p> <ul style="list-style-type: none"> Hardscaping includes driveways, walkways, courtyards, surface parking areas, artificial turf, and other on-site hard surfaces. Heat island effect occurs in areas that are heavily paved or urbanized and experience higher temperatures and retain heat for longer.
Great:	+1 additional point (total 3 points)	Use one or more of the strategies presented in "Good" to treat 75% of the site's non-roof hardscaping.	
References:	<ul style="list-style-type: none"> Toronto Green Standard v3 Tier I: Air Quality (AQ 2.1) (LR), (AQ4.1)(MHR) ; Tier II: Air Quality (AQ4.3) (MHR); (AQ 2.3) (LR), (AQ 4.1) (CF) LEED ND (v4) GIB: Heat Island Reduction LEED BD+C (v4) SS: Heat Island Reduction Thinking Green (2018): 8 (Site Plan) 		

IB-8: HEAT ISLAND REDUCTION: ROOF

Intent:	To reduce ambient surface temperatures and reduce the urban heat island effect, which contributes to climate adaptation and more comfortable, livable communities.		
Applicable to:	<input type="checkbox"/> Block Plan	<input type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Great:	2 points	Cool roof installed for 100% of the available roof space.	On a Landscape Plan, Elevation drawings, or Roof Plan: <ul style="list-style-type: none">Determine the area of Available Roof Space.For Cool Roof products, provide examples of the products that are intended for the design and provide manufacturer's documentation with the SRI or solar reflectance value to confirm.Determine the percent (%) area of roofing surfaces treated with a cool roof, green roof and/or solar PV as a percent (%) of the total available roof space. Note: <ul style="list-style-type: none">Available roof space for cool roof areas consists of the total roof area of the building or building addition excluding private terraces no greater in area than the floor of the abutting residential unit at the roof level.Available Roof Space is defined as the total roof area minus the areas designated for renewable energy, residential private terraces, residential outdoor amenity spaces (to a maximum of 2 square metres per unit, and a tower roof on a building with a floor plate less than 750 square metres. The definition is from the City of Toronto Green Roof Bylaw.Cool roofing materials have a minimum initial reflectance of 0.65 and minimum emittance of 0.90 or a three-year aged SRI value of 64 for a low-sloped roof and a three-year aged SRI of 15 for a steep-sloped roof. Low sloped roofs have a surface slope of less than 1:6 (9.5 degrees) and steeply sloped roofs have a surface slope greater than 1:6 (9.5 degrees).Heat island effect occurs in areas that are heavily paved or urbanized and experience higher temperatures and retain heat for longer.
Great:	4 points	Green roof installed for 50% of the available roof space.	
Excellent	+2 additional points (total 6 points)	Green roof installed for 75% of the available roof space.	
References:	<ul style="list-style-type: none">LEED ND (v4) GIB: Heat Island ReductionLEED BD+C (v4) SS: Heat Island ReductionToronto Green Standard v3, Tier I: Air Quality (AQ4.2) (CF, MHR); (AQ 2.2) (LR)Whitby Green Standard v1 (2020): LUN1.5, LUN1.8 (Site Plan)Thinking Green Item (2018): 9 (Site Plan)		

IB-9: SOLAR GAIN CONTROL

Intent:	To control solar heat gains through east and west facing windows.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	For a low-rise development: Provide exterior shading by planting at least one deciduous tree that can grow up to 50 to 70 cm DBH per lot on the west side of each low density residential dwelling.	On the Landscape Plan: <ul style="list-style-type: none"> Identify the new trees to be placed on the west side of each residential dwelling.
Great:	2 points	Provide exterior shading for all east and west facing windows.	On Elevation Drawings, identify the exterior shading method that will be used on all east and west facing windows. Note: <ul style="list-style-type: none"> Acceptable exterior shading includes operable shutters, overhangs, brise soleil canopy, awnings, solar blinds, screens, horizontal louvers and jalousies.
References:	<ul style="list-style-type: none"> Durham Region Climate Resilient Standard for New Houses (Draft 2018), Extreme Heat Protection Measures; Shading, Glazing, and Window Operability #2. 		

IB-10: SOLAR READINESS

Intent:	To encourage the use of renewable energy and reduce reliance on fossil fuel-based energy. Solar energy can provide cost-effective methods to reduce energy use and will have strong climate change benefits.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Great: (Site Plan only)	3 points	All buildings in the project are designed for solar readiness.	<p>Provide a Letter of Commitment from a qualified professional (e.g. architect, energy, structural, electrical or mechanical engineer) and the owner/developer/builder that confirms all new buildings will be designed for solar readiness.</p> <p>Note: Designing for solar readiness may include the following:</p> <ul style="list-style-type: none"> • Designate an area of the roof for future solar PV and/or solar thermal. • Design and build an adequate structural capacity of the roof structure. • Install one or two conduits from the roof to the main electrical or mechanical room (size of conduit to be determined based on maximum potential solar PV or solar thermal system size). • Designate a 2 metre by 2 metre wall area in the electrical and mechanical rooms for future solar electrical/thermal equipment controls and connections (e.g. meters, monitors). • Place the HVAC or other rooftop equipment on the north side of the roof to prevent future shading. <p>For more guidance on solar readiness, or to access a Solar Readiness Checklist, consult with NRCan Solar Ready Guidelines. Applicants are also encouraged to consult the National Renewable Energy Laboratory's Solar Ready Buildings Planning Guide for additional considerations for PV-ready provisions.</p>
Great:	2 points	In the project, 1% of the total energy is generated on-site by renewable energy sources.	<p>Provide a Letter of Commitment from a qualified professional (e.g. architect, electrical engineer, mechanical engineer, energy modeller) and the owner/developer/builder to confirm the percent (%) of renewable energy that will be included on-site. The percent (%) of renewable energy generated can be quantified by the following steps:</p> <ul style="list-style-type: none"> • List the types of buildings (office, commercial, retail, residential multi-unit and/or single-unit). • Determine the total gross floor area (GFA) for each building type and list the expected/approximate energy use intensities (EUIs) for each building type. • Determine the total building annual energy use for the site. • List the renewable energy technologies being considered for the site. • Determine the expected annual energy generated from renewable technologies and the percent (%) of annual energy generated on-site, relative to the total energy consumed.

Excellent	+1 additional point per percent (%) up to 5% (total 7 points)	In the project, more than 1% of the total energy is generated on-site by renewable energy sources.	<p>Note:</p> <ul style="list-style-type: none"> • Allowable forms of renewable energy sources include the following: • Solar photovoltaics (PV) technologies (e.g. solar panel, solar shingles), • Solar thermal, • Biogas and biofuel, • Wind-based systems. • For greater clarity, it should be noted that geo-exchange systems (e.g. ground-source heat pumps) are considered a building energy efficiency measure, as opposed to a form of renewable energy generation. As such, these systems cannot be used for the on-site renewable energy requirement, but can instead be utilized to meet the energy efficiency targets. • The renewable energy calculations can be conducted either within the whole-building energy modelling software or through recognized third-party energy modelling tools such as RETScreen Expert or PVSyst. • Off-site solutions such as renewable energy certificates (RECs), carbon offsets, or power purchasing agreements (PPA) with renewable energy generators are not permitted to satisfy this measure unless otherwise approved by the City.
Good Target (Draft Plan only)	3 points	For greenfield sites that provide ground-oriented development, 100% of dwellings in the project are designed for solar readiness.	<p>Provide a Letter of Commitment from a qualified professional (e.g. architect, energy, structural, electrical or mechanical engineer) and the owner/developer/builder confirming that:</p> <ul style="list-style-type: none"> • All dwellings in the project will be designed for solar readiness.
References:	<ul style="list-style-type: none"> • NRCAN Solar Ready Guidelines • Toronto Green Standard v3 Tier II: Energy Efficiency, GHG & Resilience (GHG 2.1) (CF, MHR), (GHG 2.2) (LR) • Whitby Green Standard v1 (2020): ECC1.2, ECC.V.1 (Draft Plan of Subdivision); ECC1.2, ECC.V.1, ECC.V.2, ECC.V.3 (Site Plan) • Thinking Green Item (2018): 13 (Draft Plan of Subdivision); 16 (Site Plan) 		

IB-11: ENERGY STRATEGY

Intent:	To encourage the early consideration and incorporation of sustainable design features in the planning process relating to improved building energy efficiency, carbon reduction, and resilience, as well as to take advantage of district-scale opportunities in the case of multi-building developments.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Great:	3 points	<p>Develop an Energy Strategy for the proposed development that includes the following, as applicable:</p> <ul style="list-style-type: none"> • High-level energy analysis using archetype modelling or benchmarking data to estimate the overall energy consumption and GHG emissions associated with the development. • Identify and evaluate opportunities to reduce energy use intensity (EUI) and greenhouse gas 	<p>An Energy Strategy Report in accordance with a Terms of Reference that has been agreed upon by the City, and at a minimum, includes the following information:</p> <ul style="list-style-type: none"> • Executive Summary • Energy calculations, including data and assumptions • Graphs of expected energy performance • Conclusions / Recommendations • Appendices: supporting documentation, references, etc.

		<p>emission (GHG) intensity down to a net-zero ready level of performance through various measures, such as more efficient building form and massing, orientation, improved building envelope performance, highly efficient HVAC systems, heat recovery, and lighting solutions.</p> <ul style="list-style-type: none"> • Analysis of low-carbon energy solutions and on-site renewable energy generation potential that can be incorporated into the development, such as rooftop photovoltaic (PV), geo-exchange systems, high-efficiency combined heat and power (CHP), thermal energy stores, and sewer water heat recovery. • Identify and evaluate opportunities for backing power systems and passive design features that will improve the resilience of buildings to area-wide power outages. <p>For multi-unit development, also conduct the following:</p> <ul style="list-style-type: none"> • In the case of multi-building development proposals or in intensification areas identified by the City, investigate the feasibility of shared energy solutions, such as the development of low-carbon thermal energy networks or connection to planned or existing district energy systems, and identify the required provisions to be district energy-ready. 	
Excellent:	+6 additional points (total 9 points)	<p>In addition to developing an Energy Strategy, commit to meeting an energy use intensity (EUI) and greenhouse gas emissions intensity (GHGI) target for the site that strives towards a near-net zero emissions level of performance as agreed upon with the City.</p> <p style="text-align: center;">AND</p> <p>Develop a zero-carbon transition plan that lays out the pathway towards achieving carbon neutrality in the future through a variety of design measures, such as providing the necessary infrastructure for full building electrification and avoidance of on-site combustion of fossil fuels.</p>	<p>Provide an Energy Strategy report, as well as Letter of Commitment signed by the owners/developers/builders indicating commitment to meet a development-wide energy use intensity and greenhouse gas emissions intensity targets, as well as a zero-carbon transition plan that lays out specific design measures that will be incorporated to facilitate achievement of carbon neutrality in the future (for example, providing electrical infrastructure provisions to allow for full building electrification).</p>
References:	<ul style="list-style-type: none"> • City of Toronto Energy Strategy Report - Terms of Reference 		

IB-12: BUILDING ENERGY EFFICIENCY, GREENHOUSE GAS REDUCTION, AND RESILIENCE

Intent:	To promote buildings that are designed to be energy-efficient with reduced operating costs and greenhouse gas emissions associated with building operations, while improving the thermal comfort of occupants and enhancing building resilience. Well-designed buildings that are energy-efficient can improve indoor and outdoor air quality and reduce greenhouse gas emissions.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	3 points	<p>Residential buildings that are 3 storeys or less and less than 600 square metres (m²) in gross-floor building area (Part 9 Residential Buildings). <i>(Applicable to Residential only)</i> Design the building(s) to achieve ENERGY STAR® for New Homes version 17.1, R-2000® requirements, or equivalent.</p> <p>Multi-Unit Residential, Office and Retail buildings that are more than 3 storeys or greater than 600 square metres (m²) in gross-floor building area (Part 3 Buildings – Multi-Unit Residential, Office and Retail). <i>(Applicable to Mix-Used only)</i> Develop a whole-building energy model, and design and construct the building to achieve the following whole-building performance metrics:</p> <ul style="list-style-type: none"> Total Energy Use Intensity (TEUI): 170 kWh/m²/yr Thermal Energy Demand Intensity (TEDl): 70 kWh/m²/yr Greenhouse Gas Emissions Intensity (GHGI): 20 kgCO₂/m²/yr. <p>All Other Part 3 Buildings <i>(Applicable to ICI only)</i> Develop a whole-building energy model, and design and construct the building to achieve at least a 15% improvement in energy efficiency over the Ontario Building Code (OBC) SB-10, Division 3 (2017) reference building.</p>	<ul style="list-style-type: none"> Provide a Letter of Commitment signed by a qualified professional (e.g. professional engineer, architect, etc.) and the owner/developer/builder that includes confirmation that requirements of this metric will be met. Upon completion of construction, provide a Letter of Certification signed by an accredited professional that the metric requirements have been implemented and verified. <p>Site Plan Approval (SPA) Energy Model Documentation Requirements:</p> <ul style="list-style-type: none"> Energy Model Report summarizing key modelling inputs, outputs, and assumptions, signed by a licensed professional. Working Energy Model Simulation Files. Mechanical and Electrical Design Brief. Related supporting drawings and calculations done externally from the energy modelling software (for example, thermal bridging calculations). <p>As-Built Energy Model Documentation Requirements:</p> <ul style="list-style-type: none"> Updated Energy Model Report. Working Energy Model Simulation Files. Mechanical and Electrical Design Brief. Modelling Note: General, Building Level, Plant Level, System Level, Occupancy and Minimum Outdoor Air Rates, Warnings and Errors. Take-off Calculations (Modeller's external calculations to support the model inputs). If applicable, the calculation for model workarounds, exceptions, process energy savings, renewable energy systems, district energy systems, or other required calculations. Zoning Diagrams. Outdoor Air Calculation Spreadsheets. Architectural Drawings and Specifications (issued for construction/as-built). Mechanical Drawings and Specifications (issued for construction/as-built). Electrical Drawings and Specifications (issued for construction/as-built).
Great:	+4 additional points (total 7 points)	<p>Residential buildings that are 3 storeys or less and less than 600 square metres (m²) in gross-floor building area (Part 9 Residential Buildings). <i>(Applicable to Residential only)</i></p>	

		<p>Design, construct, and label the building(s) to achieve ENERGY STAR® for New Homes version 17.1, R-2000® requirements, or equivalent.</p> <p>Multi-Unit Residential, Office and Retail buildings that are more than 3 storeys or greater than 600 square metres (m²) in gross-floor building area (Part 3 Buildings – Multi-Unit Residential, Office and Retail). <i>(Applicable to Mix-Used Only)</i></p> <p>Develop a whole-building energy model, and design and construct the building to achieve the following whole-building performance metrics:</p> <ul style="list-style-type: none"> • Total Energy Use Intensity (TEUI): 135 kWh/m²/yr • Thermal Energy Demand Intensity (TEDI): 50 kWh/m²/yr • Greenhouse Gas Emissions Intensity (GHGI): 15 kgCO₂/m²/yr <p>All Other Part 3 Buildings <i>(Applicable to ICI only)</i></p> <p>Develop a whole-building energy model, and design and construct the building to achieve at least a 25% improvement in energy efficiency over the Ontario Building Code (OBC) SB-10, Division 3 (2017) reference building.</p>	<p>Note:</p> <ul style="list-style-type: none"> • For TEUI and TEDI Energy Modelling Guidelines, please refer to the ZCB Energy Modelling Guidelines: https://www.cagbc.org/cagbcdocs/zerocarbon/CaGBC_EMG_for_ZCB_v01.pdf • For rules on carbon accounting and calculating GHGI, please refer to the Zero Carbon Building Standard: https://www.cagbc.org/cagbcdocs/zerocarbon/CaGBC_Zero_Carbon_Building_Standard_EN.pdf
Excellent:	+6 additional Points (total 13 points)	<p>Residential buildings that are 3 storeys or less and less than 600 square metres (m²) in gross floor area (Part 9 Residential Buildings). <i>(Applicable to Residential only)</i></p> <p>Design and construct the building(s) to be Net Zero ready in accordance with the CHBA Net Zero Home Labelling Program, or equivalent.</p> <p>Multi-Unit Residential, Office and Retail buildings that are more than 3 storeys or greater than 600 square metres (m²) in gross-floor building area (Part 3 Buildings – Multi-Unit Residential, Office and Retail). <i>(Applicable to Mix-Used Only)</i></p> <p>Develop a whole-building energy model and design the building to achieve the following whole-building performance metrics associated with a near-net zero emissions level of performance:</p> <ul style="list-style-type: none"> • Total Energy Unit Intensity (TEUI): 100 kWh/m²/yr • Thermal Energy Demand Intensity (TEDI): 30 kWh/m²/yr 	

		<ul style="list-style-type: none"> Greenhouse Gas Emissions Intensity (GHGI): 10 kgCO₂/m²/yr <p>All Other Part 3 Buildings <i>(Applicable to ICI only)</i> Develop a whole-building energy model and design the building to achieve at least a 37% improvement in energy efficiency over the Ontario Building Code (OBC) SB-10, Division 3 (2017) reference building.</p>	
Exceptional	+8 additional points (total 21 points)	<p>Residential buildings that are 3 storeys or less and less than 600 square metres (m²) in gross-floor building area (Part 9 Residential Buildings). <i>(Applicable to Residential only)</i> Design and construct the building(s) in accordance with the CHBA Net Zero Homes Labelling Program, or Passive House standards, or equivalent.</p> <p>Multi-Unit Residential, Office and Retail buildings that are more than 3 storeys or greater than 600 square metres (m²) in gross-floor building area (Part 3 Buildings – Multi-Unit Residential, Office and Retail). <i>(Applicable to Mix-Used Only)</i> Develop a whole-building energy model and design the building to achieve the following whole-building performance metrics associated with a near-net zero emissions level of performance:</p> <ul style="list-style-type: none"> Total Energy Unit Intensity (TEUI): 75 kWh/ m²/yr Thermal Energy Demand Intensity (TEDI): 15 kWh/m²/yr Greenhouse Gas Emissions Intensity (GHGI): 5 kgCO₂/m²/yr <p>All Other Part 3 Buildings <i>(Applicable to ICI only)</i> Develop a whole-building energy model and design the building to achieve at least a 50% improvement in energy efficiency over the Ontario Building Code (OBC) SB-10, Division 3 (2017) reference building.</p>	

Good:	3 points	<p>Metering Install electricity and/or thermal sub-meters for all energy end-uses that represent more than 10% of the building's total energy consumption, following the requirements laid out in LEED v4 Reference Guide Advanced Energy Metering credit.</p> <p>For buildings with multiple tenants, provide energy sub-metering for each commercial/institutional tenant, and per residential suite.</p>	<p>Provide electrical and mechanical single line diagrams that indicate the provision of electricity and thermal sub-meters.</p> <p>A metering plan listing all meters along with type, energy source metered, diagrams, and/or references to design documentation.</p>
Great:	3 points	<p>Building Commissioning Conduct best practice commissioning, per the requirements referenced in LEED BD+C v4 Fundamental Commissioning and Verification pre-requisite.</p> <p>(Building commissioning is a systematic process of verifying that the various building sub-systems such as building envelope, mechanical (HVAC), plumbing and lighting systems are constructed and operational per the project requirements and design intent.)</p>	<p>Provide a Letter of Commitment signed by the owner/developer/builder confirming that building commissioning will be carried out per the requirements of LEED v4 BD+C Fundamental Commissioning and Verification pre-requisite.</p>
Excellent:	4 points	<p>Airtightness Testing Conduct a whole-building air leakage test to improve the quality and airtightness of the building envelope.</p>	<p>Provide Letter of Commitment signed by the owner/developer/builder that an airtightness testing provider will be retained to conduct a whole-building air leakage test.</p> <ul style="list-style-type: none"> It is recommended that applicants follow ASTM WK35913 Standard Test Method for Determining the Air Leakage Rate of Large or Multi-zone Buildings or US Army Corps of Engineers (USACE) Air Leakage Test Protocol. Projects will conduct an operational envelope airtightness test under negative pressure producing a multi-point regression. However, projects are permitted to pursue negative and positive pressure testing and produce a building envelope test where HVAC-related openings are excluded as in the Passive House standard. Projects will target a test pressure of 75Pa. Projects unable to achieve 75Pa must follow either ASTM W35913 alternative test methods; Repeated Single-Point Test or a Repeated Two-Point test and demonstrate compliance using projected curves for airtightness at 75Pa. If the whole building cannot be tested as one zone, it is acceptable to test a zone that can be partitioned temporarily with adjacent zones "Guarded" as buffer zones using blower door equipment. Note that the air leakage rate should be normalized to the exterior surface area and not include the guarded surface areas. All materials, assemblies, and systems that form the continuous air barriers systems must be installed including any HVAC equipment, ducts, and fittings included in the test boundary. Upon completion, the applicant shall provide a completed airtightness testing report to City officials. For low-rise developments, conduct airtightness testing for 15 percent of the dwelling.

References:	<ul style="list-style-type: none"> Toronto Green Standard v3: Energy Efficiency, GHG & Resilience (CF, LR, MHR) Whitby Green Standard v1 (2020): ECC1.4, ECC1.5, ECC1.6, ECC1.7, ECC.V.4, ECC.V.6 Thinking Green Item (2018): 13 (Site Plan)
--------------------	---

IB-13: RAINWATER AND GREYWATER USE

Intent:	To reduce potable water use for interior building functions.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	<p>Rainwater or greywater is captured on-site and used for exterior uses (e.g. landscape irrigation).</p> <p>AND</p> <p>Buildings are designed for rainwater and/or greywater use readiness (e.g. plumbing infrastructure rough-ins or dedicated cistern space for rainwater or greywater use or greywater irrigation that may be connected in the future are included in the building).</p>	<p>Rainwater Use for Exterior Functions</p> <ul style="list-style-type: none"> On the Site Servicing Plan and Landscape Plan identify the type and location of rainwater capture/use infrastructure. <p>Greywater Use for Exterior Functions</p> <ul style="list-style-type: none"> On the Site Servicing Plan and Landscape Plan identify the type and location of greywater capture/use infrastructure. <p>Greywater and/or Rainwater Use for Interior</p> <ul style="list-style-type: none"> A Letter of Commitment signed by a qualified professional (e.g. architect, engineer) and the owner/developer/builder committing that the project will either be designed to provide greywater and/or rainwater use for internal functions, specifying which internal functions and the potential technology/infrastructure that will be used.
Great:	+3 additional points (total 4 points)	<p><i>Greywater Use for Interior Functions</i> Greywater is captured on site, treated, and used for toilet and urinal flushing, as well as priming flood drains within a home.</p> <p>OR</p> <p><i>Rainwater Use for Interior Functions</i> Rainwater is captured on site and used for toilet and urinal flushing.</p>	<p>Note:</p> <ul style="list-style-type: none"> <i>Greywater</i> is wastewater generated from dish washing, hand washing, laundry, bathing and showering. All Greywater and Rainwater use must comply with the Ontario Building Code. To be awarded a point for the 'Good' metric, both requirements must be met
References	<ul style="list-style-type: none"> Thinking Green (2018): 19 (Site Plan) 		

IB-14: BACK-UP POWER

Intent:	To encourage the provision of back-up power that enables the functioning of key utilities/building functions during power failures resulting from extreme weather events.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	Provide rough-ins to allow for the installation of external generators/auxiliary power supply at a later date.	<p>Provide a Letter of Commitment stating that all residential dwellings will be provided rough-ins to allow for the installation of external generators/auxiliary power supply at a later date.</p> <p>Note:</p> <ul style="list-style-type: none"> Applies to all residential building types.
Good	1 point	For mid-rise and high-rise buildings, provide a refuge area with heating, cooling, lighting, potable water, and power available for 72 hours.	<p>On the Floor Plans, identify the common refuge area.</p> <p>Provide a Letter of Commitment stating that the refuge area will be provided and supplied with heating, cooling, lighting, potable water, and power available for 72 hours.</p> <p>Note:</p> <ul style="list-style-type: none"> Applies to residential buildings that contain central amenity/lobby space. A refuge area should be a minimum size of 93 square metres (m²) (1000 square feet (ft²)), and/or 0.5m²per occupant and may act as building amenity space during normal operations. Common refuge areas are temporarily shared, lit spaces where vulnerable residents can gather to stay warm or cool, charge cell phones and access the internet, safely store medicine, refrigerate basic food necessities, access potable water and toilets, and perhaps prepare food.
Great	3 points	Provide 72 hours of back-up power to essential building systems.	<p>Provide a Letter of Commitment stating that at least 72 hours of back-up power to essential building systems will be provided.</p> <p>Note:</p> <ul style="list-style-type: none"> Provide a 72 hour minimum back-up power system, preferably using a non-fossil fuel source, to ensure power is provided to the refuge area, building security systems, domestic water pumps, sump pumps, at least one elevator, boilers and hot water pumps to enable access and egress and essential building functions during a prolonged power outage. Applies to multi-unit residential buildings only.
References:	<ul style="list-style-type: none"> Durham Region Climate Resilient Standard for New Houses (Draft 2018), Basement Flood Protection Measures; Enhanced Protection #18 Toronto Green Standard v3 Tier II: Energy Efficiency, GHG & Resilience (GHG 5.2) (CF, MHR) City of Toronto. Minimum Backup Power Guidelines for MURBs, Voluntary Performance Standards for Existing and New Buildings (2016). City of Brampton. Emergency Preparedness Guide. 		

- Whitby Green Standard v1 (2020): ECC.V.7 (Site Plan)

IB-15: EXTREME WIND PROTECTION FOR GROUND-ORIENTED DEVELOPMENT

Metric Intent: To increase the resistance of homes to the impacts of high wind events, and make them more resilient to the impacts of climate change.

Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional

	Points	Requirement	Documentation
Good:	2 points	<p>Roof to Wall Connections:</p> <ul style="list-style-type: none"> Tie roof rafters, roof trusses or roof joists to load-bearing wall framing in a manner that will resist a factored uplift load of 3 kilo Newton's (kN). This measure requires adequate connection of the top plate to the supporting wall studs, combined with adequate continuous vertical load path. If continuous structural wall sheathing (see Measure A.2.3) is not applied, then a top-to-bottom inspection to address all potential weak links in the continuous vertical load path using additional tires, straps or related measures should be applied. <p style="text-align: center;">AND</p> <ul style="list-style-type: none"> When engineered connectors are used, builders should request that truss manufacturers supply appropriate roof-to-wall connections along with trusses. <p>Stud to Sill Plate Connection</p> <ul style="list-style-type: none"> Installation of metal straps or connectors to connect lower storey wall studs to the sill plate. 	<p>Provide a Letter of Commitment from a qualified professional (e.g. architect, structural, electrical or mechanical engineer) stating that roof to wall, and stud to sill plate connections will be provided as specified in this metric.</p> <p>Note:</p> <ul style="list-style-type: none"> Builders should request that truss manufacturers supply appropriate roof-to-wall connectors along with trusses. To be awarded a point for the 'Good' metric, both requirements must be met.
References:	<ul style="list-style-type: none"> Institute for Catastrophic Loss Reduction, Increasing High Wind Safety for Canadian Homes: A Foundational Document for Low-Rise Residential and Small Buildings (2019) Sandink, D., et al. Increasing High Wind Safety for Canadian Homes: A Foundational Document for Low-Rise Residential and Small Buildings. (April 2019) Whitby Green Standard v1 (2020): ECC1.8 (Site Plan) 		

IB-16: SUB-METERING OF THERMAL ENERGY AND WATER

Metric Intent:	To include sub-metering that allows measurement of individual unit consumption, which helps residents understand how their behaviour drives energy costs, and motivates change in behaviour, often resulting in reductions in energy and/or water consumption.		
Applicable to:	<input type="checkbox"/> Block Plan	<input type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	2 points	Buildings are designed to include thermal energy meters for each tenant in multi-tenant residential, commercial/retail buildings.	A Letter of Commitment signed by an accredited professional (e.g. architect, engineer) and the owner/developer to confirm that all buildings will be designed and constructed to include thermal energy meters for each unit.
Good	2 points	Buildings are designed to include water meters for each tenant in multi-tenant residential, commercial/retail buildings.	<p>A Letter of Commitment signed by an accredited professional (e.g. architect, engineer) and the owner/developer to confirm that all buildings will be designed and constructed to include water meters for each unit;</p> <p>AND</p> <p>Water meters being provided to each tenant in multi-tenant residential, commercial/retail buildings should be denoted on the Site Servicing Plan.</p>
References:	<ul style="list-style-type: none"> Toronto Green Standards v3 Tier II: Energy Efficiency, GHG & Resilience (GHG 4.4) (CF, MHR) Whitby Green Standard v1 (2020): SW.V.1, ECC.V.4 (Site Plan) LEED BD+C (v4) WE: Water Metering, EA: Advanced Energy Metering Thinking Green 2018): 20 (Site Plan) 		

IB-17: LIGHT POLLUTION REDUCTION

Intent:	To reduce nighttime glare and light trespass from building(s) and site(s). Light pollution can be perceived as an inefficient use of energy in addition to its negative impacts on neighbors and nocturnal animals.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	<p>Not applicable to Richmond Hill – alternative target provided below</p> <p>All exterior fixtures are Dark Sky Compliant</p>	<p>A Letter of Commitment from a qualified professional (architect, energy, structural, electrical or mechanical engineer), and the owner/developer/builder confirming that:</p> <ul style="list-style-type: none"> All fixtures intended for exterior lighting will be Dark Sky Compliant. <p>Note:</p> <ul style="list-style-type: none"> In alignment to the TGS v3 EC5.1 credit, the following guidance is provided for Dark Sky Compliant fixtures on the City's TGS website and can be used for this metric: Dark Sky Compliant fixture must have the <u>Dark Sky Fixture Seal of Approval</u> which provides objective, third-party certification for lighting that minimizes glare, reduces light trespass and doesn't pollute the night sky.

			<ul style="list-style-type: none"> • If a Dark Sky Fixture Seal of Approval is not available fixtures must be full-cutoff and with a colour temperature rating of 3000K or less. • All exterior light fixtures should be efficient while providing minimum illumination levels sufficient for personal safety and security. • Efficient exterior lighting is defined as 60 Lumens/Watt minimum system efficiency. • Safety and security lighting should minimize glare and/or light trespass. For more information see the Best Practices for Effective Lighting.
Good:	1 point	<p><i>For City of Richmond Hill only:</i> All exterior fixtures are to be Dark Sky Compliant and exterior lighting to comply with City of Richmond Hill Light Pollution By-Law 63-95.</p>	<p>A Letter of Commitment from a qualified professional (e.g. architect, energy, structural, electrical or mechanical engineer) and the owner/developer/builder – with supporting lighting plans, details and photometric analysis - confirming that:</p> <ul style="list-style-type: none"> • All fixtures intended for exterior lighting will be Dark Sky Compliant • If a Dark Sky Fixture Seal of Approval is not available fixtures must be full-cutoff with a colour temperature rating of 3000K or less. • Exterior lighting complies with the City's Light Pollution By-law 63-95. • Design will not include any up-lighting • No architectural lighting will be used between 11pm and 5am <p>Note:</p> <ul style="list-style-type: none"> • Architectural lighting is considered façade or rooftop decorative lighting. Emergency and safety lighting are not considered architectural lighting. • All exterior light fixtures should be efficient while providing minimum illumination levels sufficient for personal safety and security • Efficient exterior lighting is defined as 60 Lumens/Watt minimum system efficiency • Safety and security lighting should minimize glare and/or light trespass. For more information see the Best Practices for Effective Lighting <p>For further guidance, see Light Pollution By-Law 63-95.</p>
Great:	1 point	<p><i>For City of Richmond Hill only:</i> Develop lighting controls that reduce night time spillage of internal light by 50% from 11pm to 5am</p> <p><u><i>(Applicable to Mixed-Use and ICI only)</i></u></p>	<p>A Letter of Commitment from a qualified professional (e.g. architect, energy, structural, electrical or mechanical engineer) that details the:</p> <ul style="list-style-type: none"> • Types of devices used (e.g. lighting controls, timers) or measure taken (e.g. shielding openings in building envelope) • Level/amount of reduction • Time period during which light would be reduced <p>Note:</p> <ul style="list-style-type: none"> • Applicable to non-residential development only
References:	<ul style="list-style-type: none"> • ANSI/IES LP-11: Lighting Practice: Environmental Considerations for Outdoor Lighting • LEED ND (v4) GIB: Light Pollution Reduction • LEED BD+C (v4.1) SS: Light Pollution Reduction • Toronto Green Standard v3 Tier 1: Ecology (EC5.1) (CF, LR, MHR); Tier 2: Ecology (EC 5.3) (MHR) • City of Vaughan Urban Design Guidelines • City of Markham Bird Friendly Guidelines • City of Richmond Hill Light Pollution By-Law 		

IB-18: BIRD-FRIENDLY BIRD-SAFE DESIGN

Intent:	To reduce incidents of bird collisions and provide an urban environment where birds can thrive. The built environment can have strong negative impacts on birds; design and system selection can result in fewer bird collisions and deaths.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	2-points	<p>Not applicable to Richmond Hill – alternative metric provided below</p> <p>A combination of Bird-Friendly Design strategies on at least 85% of contiguous glass area greater than 2 square metres (m²) within the first 16 metres of the building above-grade (including interior courtyards) and above-green roofs is applied.</p> <p>AND</p> <p>The remaining 15% of glazed windows do not need to be treated unless the glazing is larger than 2 square metres (m²) or in close proximity to open spaces, a green roof or a natural heritage feature.</p> <p>Bird-Friendly Design Strategies may include:</p> <ul style="list-style-type: none"> Visual patterns on glass, Window films, Fenestration patterns, Angled glass downwards, Reducing night sky lighting. 	<p>On the building Elevation drawings:</p> <ul style="list-style-type: none"> Highlight and declare the total area of contiguous glass, below 16 metres above grade that is greater than 2 m². Indicate the areas treated bird friendly design strategy, noting which strategy has been used. Quantify the total area of continuous glass that has been treated by bird-friendly design strategies and confirm that it is at least 85%. <p>To be awarded a point for the 'Good' metric, both requirements must be met.</p> <p>Confirm that the visual markers on the glass have spacing no greater than 10 cm x 10 cm.</p>

<p>Good:</p> <p><i>(this metric is mandatory for Site Plan and strongly encouraged for Draft Plan applications)</i></p>	<p>2 points</p>	<p><i>For City of Richmond Hill only:</i></p> <p>Apply Bird-Safe Standards to 100% of glazing:</p> <ul style="list-style-type: none"> • within the first 16 metres of the building above-grade (or the height of adjacent mature tree canopy, whichever is greater) • within 4m above green roofs (or the height of adjacent vegetation, whichever is greater) • used in balconies or parapets, glass walls located in parallel, including bridges and enclosed elevated walkways • located at building corners at successive floors spanning 5m in each direction (laterally) <p>AND</p> <p>All development contains no non-glass material that has a greater than 15% reflectivity within 16m from finished grade or to the height of adjacent mature tree canopy, whichever is greater.</p>	<p>On separate Bird-Safe elevation drawings:</p> <ul style="list-style-type: none"> • Show treated glazing at grade condition, roof landscape condition, and specifications and include the Bird-Safe Specifications Checklist <p>Confirm that the visual markers on the glass have:</p> <ul style="list-style-type: none"> • Spacing no greater than 5 cm x 5 cm • Dot size is a minimum of 4 mm in diameter, or • Linear elements are a minimum of 2mm wide x 8mm long, or • Pattern is applied as fritting or etching of glass and pattern colour are in high contrast in relation to the background, or • Pattern is applied as film on exterior surface of glass and pattern colour are high contrast in relation to the background <p>For further guidance, see: Richmond Hill Bird-safe Design Standards</p>
<p>Good:</p>	<p>2 points</p>	<p>Apply Bird-Friendly-Safe Design strategies for ground-oriented residential development that is adjacent to natural heritage systems and open spaces.</p> <p><u><i>(Applicable to Residential and Mixed-Use only)</i></u></p>	<p>Provide a Letter of Commitment signed by an accredited professional (architect or professional engineer) and the owner/developer that confirms Bird Friendly Design strategies are incorporated for developments adjacent to natural heritage systems and open spaces, listing which acceptable Bird Friendly Design strategies are to be included.</p>
<p>References:</p>	<ul style="list-style-type: none"> • City of Richmond Hill: Bird-Safe Design Standards 2024 • City of Vaughan: Urban Design Guidelines • City of Markham Bird Friendly Guidelines • Whitby Green Standard v1 (2020): LUN1.7 (Site Plan) • Toronto Green Standard v3 Tier I: Ecology (EC4.1) (CF, LR, MHR); Tier II: Ecology (EC4.3) (LR), (EC4.4) (MHR) 		

IB-19: SOLID WASTE

Intent:	To promote waste reduction and diversion of materials from landfills. A reduction in waste can be a very cost-effective method for material savings and results in fewer contributions to landfills and lower carbon emissions due to savings in materials.		
Applicable to:	<input type="checkbox"/> Block Plan	<input type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement	Documentation
Good:	1 point	A waste system for garbage, recycling, and organics is provided using one or more of the following options: <ul style="list-style-type: none"> Three separate chutes for garbage, recycling, and organics collection on all floors. 	<p>On the Site Plan and/ or Floor Plans:</p> <ul style="list-style-type: none"> Identify the waste systems for garbage, recycling, and organic waste. <p>Note:</p> <ul style="list-style-type: none"> The requirements apply to residential developments with 33 units or more and building heights greater than 5 storeys.
Good:	1 point	<p>Not applicable to Richmond Hill because this is already a municipal requirement (see Waste by-law 18-19 for more details)</p> <p><i>Residential:</i> Accessible waste storage room with minimum 25 square metres (m²) floor space for the first 50 units, plus an additional 13 square metres (m²) for each additional 50 Units to accommodate containers and compactor units is provided.</p> <p><i>Non-residential:</i> Provide a fully enclosed waste storage space to accommodate garbage and materials diversion of recycling and organics.</p>	<p>On the Site Plan and/ or Floor Plans:</p> <ul style="list-style-type: none"> Identify waste storage areas. Determine the floor area provided for the waste storage space and identify the separate garbage storage, recycling storage, and organics storage, (Residential only): Determine the waste storage area required based on the number of dwelling units and declare on Floor Plans/ Site Plan drawing.
Good:	1 point	<p>Not applicable to Richmond Hill because this is already a municipal requirement (see Waste by-law 18-19 for more details)</p> <p>A minimum of 10 square metres (m²) for bulky items and items eligible for special collection services is provided.</p>	<p>On a Site Plan and/ or Floor Plans:</p> <ul style="list-style-type: none"> Identify the storage for bulky items and declare the area. The 10m² may not be shared with other purposes and be solely dedicated to bulky waste to meet this target, although it may be in the same room as other waste storage. <p>Note:</p> <ul style="list-style-type: none"> Bulky items are household items greater than 1.2 metres in any one dimension or weigh more than 20 kg (including furniture).
Great: (Residential and Mixed-Use only)	1 point	<p>Not applicable to Richmond Hill because this is already a municipal requirement (see Waste by-law 18-19 for more details)</p>	<p>On a Site Plan and/ or Floor Plans,</p> <ul style="list-style-type: none"> Identify the dedicated collection area or room for the collection of household hazardous waste and/or electronic waste. <p>Note:</p>

		<i>Residential only:</i> Provide a dedicated collection area or room for the collection of household hazardous waste and/or electronic waste.	Household Hazardous Waste (HHW) includes car products, motor oil, windshield fluid; household cleaning products; paint, glue, primers, stains; pesticides and garden products; cooking oil; batteries; propane tanks; CFLs, syringes, medical sharps; medication; air fresheners, swimming pool chemicals.
References:	<ul style="list-style-type: none"> • Toronto Green Standard v3 Tier I: Solid Waste (SW1.1, SW1.2, SW1.3) (MHR); Tier II: Solid Waste (SW1.6) (MHR), (SW 1.2) (LR) • Whitby Green Standard v1 (2020): ZW1.1, ZW1.2 (Site Plan) • Thinking Green (2018): 34 (Site Plan) 		

INNOVATION

I-1: INNOVATION

Intent:	To encourage applicants to achieve innovative performance. Innovation strategies must demonstrate a comprehensive approach, have significant, measurable environmental benefits, and be better than standard practice.		
Applicable to:	<input type="checkbox"/> Block Plan	<input checked="" type="checkbox"/> Draft Plan of Subdivision	<input checked="" type="checkbox"/> Site Plan
	<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Mixed-Use	<input checked="" type="checkbox"/> Industrial, Commercial, Institutional
	Points	Requirement & Documentation	
Exceptional:	Up to a total of 10 points based on the measurable sustainability benefit provided (additional points be awarded at the discretion of the City)	<p>The proposed innovation metric must demonstrate a quantitative improvement in sustainable performance by identifying or establishing a baseline of standard performance and comparing that benchmark with the final design performance. Should this Innovation Metric be pursued by an applicant, as part of first submission, the applicant must provide a high-level concept of the proposed Innovation metric for review by the City. This concept should include a description of the sustainability benefit being pursued and the proposed point allocation.</p> <p>Applicants may choose to explore innovative measures listed in the Innovation Library as detailed below and must indicate this as part of their submission. As part of the application review process of the first submission, the City will then provide a response as to whether the applicant's proposal will be considered further.</p> <p>Should the applicant's proposal be considered acceptable by the City to pursue further, applicants shall be required to demonstrate the following to the satisfaction of the City as part of the second submission.</p> <p>The applicant must explain in detail the benefit of the proposed innovation metric and submit:</p> <ul style="list-style-type: none"> • The intent of the proposed innovation metric, • The proposed requirements for compliance, • The proposed submittals to demonstrate compliance, • The design approach to strategies used to meet the requirements. <p>Innovation points will only be considered for strategies not already identified in the menu of metric options. Innovation points are not awarded for the use of a particular product or design strategy if the technology aids in the achievement of an existing metric, even if the project is not attempting to earn that metric. Corporate strategies are not considered innovative for the purposes of this metric.</p> <p><i>The Innovation Library</i></p> <ul style="list-style-type: none"> • Idea #1 - Include on the site, a Tall Wood Building, an exemplary performance of the intent behind Embodied Carbon metric and a demonstration of leadership in tall wood construction. A tall wood building is defined as a building over 6 storeys that uses wood for its structural system and is built using mass timber construction. Tall wood building projects with mass timber require alternative solutions for approval under Ontario Building Code. Ontario's Tall Wood Building Reference (2017) is a technical resource to help applicants with how tall wood buildings can be designed as alternative solutions in a way that achieves the level of performance required by the Ontario Building Code. • Idea #2 – Plan, design, and construct low-density residential areas such that they do not require retail natural gas service. Low-density residential dwellings will not rely on natural gas or other fossil fuel as any energy and heating source. <p>Note:</p> <ul style="list-style-type: none"> • The development proponent can also request to meet with the City to discuss a potential innovation metric prior to the Pre-Consultation submission. • The applicant may be required to provide detailed information regarding anticipated future long-term costs (financial and otherwise) and maintenance needs for the proposed innovative feature(s). 	

References:	<ul style="list-style-type: none">• LEED ND (v4) IN: Innovation• LEED BD+C (v4) IN: Innovation• Whitby Green Standard v1 (2020): Tier II: Innovation (Draft Plan of Subdivision, Site Plan)	